



TECHNICAL DATA SHEET

PRODUCT

INDY SUPER SYNTEC 10W40 Full Synthetic Diesel Engine Oil

DESCRIPTION

INDY Super Syntec 10W40 is a full synthetic ultra-high performance, long life diesel engine oil. INDY Super Syntec 10W40 is formulated using hydro-isomerised base oils and selected additive technology to provide extra protection even under severe operating conditions. INDY Super Syntec 10W40 contains a high level of detergents that prevents sludging and deposit accumulation, allowing for extended drain intervals. INDY Super Syntec 10W40 provides excellent oxidation stability, wear protection and corrosion control, and is formulated to fulfil EURO IV (and previous) emission standards requirements.

APPLICATION

INDY Super Syntec 10W40 is suitable for use in all diesel engines running under severe operating conditions, and is applicable to a wide range of heavy duty vehicles found in trucking, mining, construction, marine and agricultural industries.

TECHNICAL CHARACTERISTICS

API: CI4

Daimler MB 228.5
MACK EO-M Plus
VOLVO VDS-3

MTU DDC Type 3
SCANIA LDF-2
DEUTZ DQC III-05

ACEA E4/E7-08
RENAULT Truck RXD / RLD-2

Cummins CES 20077/78
MAN M3277(formal approval)

SAE Grade	10W40
Density at 20°C	kg.m ⁻³ 850 (typical)
Viscosity at 40°C	(cSt) 108.2 (typical)
Viscosity at 100°C	(cSt) 15.0 (typical)
Viscosity Index	154

PACK SIZES

1000L, 210L, 20L

Revision 2: 23 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.