



PRODUCT

INDY LSA 40
Low Ash Monograde Engine Oil

DESCRIPTION

INDY LSA 40 is a monograde engine oil blended from paraffinic base oils and ashless additive packages to provide excellent detergency, anti-wear, anti-oxidant and corrosion inhibition properties. INDY LSA 40 is suitable for use in both petrol and diesel engines requiring API CF / SF specifications.

APPLICATION

INDY LSA 40 is suitable for use in a wide variety of engines, as well as mixed fleet applications incorporating older petrol and diesel engines. INDY LSA 40 can be used for the running-in of reconditioned engines.

TECHNICAL CHARACTERISTICS

API CF/SF

SAE Grade		40	
Density at 20°C	kg.m ⁻³	890	(typical)
Viscosity at 40°C	cSt	145	(typical)
Viscosity at 100°C	cSt	14.7	(typical)
Viscosity Index		95	

PACK SIZES

210L, 25L

Revision 2: 23 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD