

PRODUCT

INDY TURBO DIESEL Diesel Engine Oil

DESCRIPTION

INDY Turbo Diesel is an SAE 15W40 grade premium diesel engine oil specially formulated with advanced additive technology to comply with API CG-4 specifications. INDY Turbo Diesel is blended from paraffinic base oils and additives incorporating anti-wear, detergency and corrosion inhibition functionalities. INDY Turbo Diesel is formulated to provide excellent stay-in-grade viscometrics even when operating under severe conditions, and is suitable for use in both turbo-charged and normally aspirated heavy duty engines.

APPLICATION

INDY Turbo Diesel is suitable for use in long-service conditions in both turbo-charged and normally aspirated heavy duty engines.

TECHNICAL CHARACTERISTICS

API CG-4/CF, API SL	ACEA04 E2	MB 228.3 (Blanket Approval)
MAN M3275-1	MTU TYPE 2	

SAE Grade		15W40	
Density @ 20°C	kg.m ⁻³	890	
Viscosity at 40°C	(cSt)	110	(typical)
Viscosity at 100°C	(cSt)	14.5	(typical)
Viscosity Index		138	
Flash Point	°C	222	
Pour Point	°C	-25	
TBN	mg KOH/g	8.5	(typical)

PACK SIZES

4*5L, 12*1L

Revision 2: 26 August 2015

Durban Head Office: + 27 31 910 3111 + 27 60 572 8088 Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.