



PRODUCT

INDY TURBO DIESEL XHD Super High Performance Diesel Engine Oil

DESCRIPTION

INDY Turbo Diesel XHD is formulated as a Super High Performance Diesel (SHPD) lubricant that has been specially developed for modern heavy duty engines. Indy Turbo Diesel XHD contains low-ash additive technology that meet requirements of Euro 3 and Euro 4/5/6 engine specifications, and is applicable for extended drain intervals. The stay-in-grade viscometrics ensures that Indy Turbo Diesel XHD has all seasonal suitability. The advanced additive technology of Indy Turbo Diesel XHD aids in maintaining engine cleanliness as well as providing superior protection for engine components.

APPLICATION

INDY Turbo Diesel XHD is suitable for use in long-service and extended-drain conditions in both turbo-charged and normally aspirated heavy duty engines.

TECHNICAL CHARACTERISTICS

API CI-4-/SL	ACEA E7-12 (2012)	MB 228.3
Volvo VDS-3	Cummins CES 20076, 20077, 20078	CAT ECF1-9
CAT ECF-2	Mack EO-N, EO-M Plus	Global DHD-1
Renault Trucks RD-2	MAN 3275-1	MTU Type 2
Detroit Diesel DDC 93K215	Deutz DQC III-10	

SAE Grade		15W40
Density at 20°C	kg.m ⁻³	870
Viscosity at 40°C	(cSt)	112 (typical)
Viscosity at 100°C	(cSt)	14.5 (typical)
Viscosity Index		132
TBN	mg KOH/g	10.7 (typical)

PACK SIZES

210L, 20L

Revision 1: 06 July 2017

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD