

SUPER TURBO DIESEL 15W40

TECHNICAL DATA SHEET

Application

- High performance engine oil specially formulated with advanced additive technology.
- Suitable for Modern Petrol & Diesel engines.
- Suitable for use in long-service conditions in both turbocharged and normally aspirated heavy duty engines.

Features & benefits

Refined Engine Cleanliness

Formulated with advanced additives incorporating anti-wear, detergency and corrosion inhibition functionalities to ensure that maximum protection against sludging and provide excellent engine cleanliness.

Advanced Engine Protection

Formulated to provide excellent stay-in-grade viscometrics even when operating under severe conditions provides excellent corrosion protection even with high sulphur levels, has a high level of wear protection and resistance to bore polishing.

- Suitable for use for the following specifications:
 - ✓ DIESEL API CI-4, CH-4, CG-4, CF-4, CF
 - PETROL API SL, SJ, SH, SG
 - ACEA E5-99, E3-96
 - ACEA A3/B3/B4-12
 - MAN M3275
 - DB 228.3/229.1
 - Volvo VDS 2
 - CAT ECF 2/1a
 - MTU Type 2
 - Mack EO-N, EO,M PLUS
 - Global DHD 1
 - Renault VI RLD-2
 - DEUTZ DQC111-10
 - **ALLISON C4 LEVEL**
 - Detroit DDC 93K 215
 - Cummins CES 20072/6/7/8
 - JASO DH-1

Physical Characteristics:

Properties		15W40 CI-4
Density @20°C	kg.m-3	890
Viscosity @40°C	(cSt)	112
Viscosity @100°C	(cSt)	14.5
Viscosity Index		132
Total Base Number	mg KOH/g	10.7

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00156	1000L
OIL-00157	210L
OIL-00158	20L
OIL-00159	4*5L
OIL-00160	12*1L
OIL-03366	20*500ML

Revision 1: November 2021 Durban Head Office: + 27 31 910 3111 Pietermaritzburg: + 27 33 392 9300 + 27 60 572 8088

+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.