



PRODUCT

INDY GREASE MS2 Multipurpose Grease

DESCRIPTION

INDY Grease MS2 is a high quality, multipurpose lithium-based grease made from solvent refined mineral oils and fortified with Molybdenum Disulfide. It incorporates a multifunctional extreme pressure additive as well as corrosion and oxidation inhibitors. It is resistant to water and high-temperature steam and suitable for operating temperatures between -30°C and 130°C.

APPLICATION

INDY Grease MS2 is designed for use in highly loaded plain and roller bearings as well as for shock loading conditions. It is suitable for use in the full range of bearing speeds encountered in electric motors, machine and woodworking tools, production equipment, textile and paper-making industry, generators and all types of vehicles. INDY Grease MS2 is recommended for all normal applications at ambient temperatures and where conditions are more severe with higher temperatures.

TECHNICAL CHARACTERISTICS

Consistency NLGI	2
Dropping Point °C	180
Viscosity at 40°C (cSt)	200
Worked Penetration @ 25°C	265/295
Colour (Visual)	Tan - Brown

PACK SIZES

180 kg / 50 kg / 15 kg / 4.5 kg / 20x500g

Revision 3: August 2017

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.