

PRODUCT

INDY NAUTICA OUTBOARD OIL 2-stroke Outboard Engine Oil

DESCRIPTION

INDY Nautica Outboard Oil is a superior performance oil, formulated to provide excellent lubrication in all two-stroke and premix outboard engines. It is based on specially designed ashless additive technology and pre-diluted with a high flash point solvent. It meets the NMMA Recertification TC-W3 specification.

APPLICATION

INDY Nautica Outboard Oil can be used in all water-cooled and oil injected two stroke marine engines. It is suitable for use with both leaded and unleaded fuels and may be used at fuel/oil mixtures of up to 100:1 subject to manufacturer's recommendation.

TECHNICAL CHARACTERISTICS

API TD NMMA: Recertified TC-W3

Density at 20°C	(kg.m⁻³)	870	(typical)
Viscosity at 40°C	(cSt) (with solvent)	210-260	(typical)
Viscosity at 100°C	(cSt) (undiluted)	18.1 – 24.5	(typical)
Ash Content	(%)	<0.01	

PACK SIZES

20 L, 4*5L, 12*1L, 20*500mL

Revision 3: 09 April 2021

Durban Head Office: + 27 31 910 3111 + 27 60 572 8088 Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.