



TECHNICAL DATA SHEET

PRODUCT

INDY SYNTRO 5W40
Full synthetic motor oil

DESCRIPTION

INDY SYNTRO 5W40 is a synthetic-based engine oil specially designed for use in high performance petrol engine applications. INDY SYNTRO 5W40 contains additives to boost performance such as detergency and stay-in-grade viscometrics, as well as providing protection in extreme conditions. The synthetic base oil provides excellent film strength under high temperatures and severe operating conditions, allowing for INDY SYNTRO 5W40 to meet even the most stringent requirements as set down by European and Japanese automotive manufacturers.

APPLICATION

INDY SYNTRO 5W40 is recommended for all high performance, high revving, turbo charged and supercharged multi-valve fuel injected petrol engines found in modern passenger cars and SUVs. INDY SYNTRO 5W40 meets the requirements for long-life oils in extended drain applications.

TECHNICAL CHARACTERISTICS

| | | |
|--------------------------------------|--------------------|-------------|
| API SN/CF | ACEA A3 /B3, B4-08 | MB 229.3 |
| VW 502 00 / 505 00 (Formal Approval) | BMW LL-01 | GM LL-B-025 |
| Porsche A40 | RN 710 / 700 | |

| | | | |
|--------------------|--------------------|------|-----------|
| SAE Grade | | 5W40 | |
| Density at 20°C | kg.m ⁻³ | 860 | (typical) |
| Viscosity at 40°C | (cSt) | 94 | (typical) |
| Viscosity at 100°C | (cSt) | 14 | (typical) |
| Viscosity Index | | 154 | |

PACK SIZES

1000L, 210L, 20L, 4*5L, 20*1L

Revision 2: 12 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD