

INDY PROTORQ 5W30

Suitable for use for the following specifications:

Application

- Recommended for use in all types of modern vehicles (petrol and diesel engines), with or without turbocharging, and in passenger cars and delivery vans with extended oil drain intervals.
- Provides exceptional performance in terms of wear protection and detergency.
- Meets the requirements for long-life oils in extended drain applications.
- Features & benefits

Refined Engine Cleanliness

Formulated with advanced additives incorporating anti-wear, detergency and corrosion inhibition functionalities to ensure that maximum protection against sludging and provide excellent engine cleanliness.

Advanced Engine Protection

Offers enhanced protection against wear, corrosion and foaming with lower fuel consumption and a fast cold start.

- API SN/CF
- Land Rover STJLR.03.5003
- Ford WSS M2C 913-C
- Ford WSS M2C 913-B
- **ACEA C3 MB 229.51**
- BMW LL-04
- VW 504 00 / 507 00

Physical Characteristics:

Properties		5W30
Density @20°C	kg.m-3	850
Viscosity @40°C	(cSt)	69.2
Viscosity @100°C	(cSt)	12.0
Viscosity Index		171

Available Product Pack Sizes:

Pack Size
1000L
210L
20L
4*5L
20*500mL

Durban Head Office: + 27 31 910 3111 **REVISION 2: OCTOBER 2022** Pietermaritzburg: + 27 33 392 9300 + 27 60 572 8088 +27 33 390 1844

> Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.