WORLD CLASS LUBRICANTS

51116

INDY SUPATEC 10W30 CF-4

SUPER TURBO DIESEL

SYNTRO

Application

- Premium motor oil formulated with advanced synthetic oil and additive technology to provide superior performance in new generation diesel engines where API CF-4 is recommended.
- Suitable for use in both normally aspirated and supercharged diesel and petrol engines.

Features & benefits

- Provides excellent lubrication at low temperatures, and advanced engine protection at extremely high temperatures.
- Offers lower oil consumption under high speed conditions.
- Enhanced protection against harmful deposits and provides excellent detergency to ensure cleanliness of components, high performance and long service life.
- Has superior wear protection and outstanding resistance to thermal breakdown at operating temperatures.

TECHNICAL DATA SHEET

Suitable for use for the following applications:

- ✓ DIESEL API CF-4/CH-4/CI-4
- PETROL API SL and all previous categories
- ✓ ACEA E7-22*
- ✓ CUMMINS CES 20076/77/71/72 & 78
- ✓ Detroit Diesel DDC93K215
- ✓ DEUTZ DQC III-10
- ✓ JASO DHD-1-17*
- ✓ GLOBAL DHD-1*
- ✓ Toyota Global Diesel
- ✓ MACK EO-N
- ✓ MAN M3275-1^L
- ✓ Daimler Trucks DTFR 15B110 (ex MB 228.3)
- ✓ MTU DDC Type 2*
- ✓ Renault Trucks RLD 2
 - VOLVO VDS 3 * All testing completed, approvals in process L Meets performance level

Physical Characteristics:

Properties		10W30
Density @20°C	kg.m⁻³	870
Viscosity @40°C	(cSt)	64.99
Viscosity @100°C	(cSt)	10.89
Viscosity Index		159.4
TBN	mg KOH/g	12.14

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00143	4*5L
OIL-00144	12*1L

Durban Head Office: + 27 31 910 3111 + 27 60 572 8088 Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.