



WORLD CLASS LUBRICANTS



INDY VORTEX 0W-20 SP/CF

TECHNICAL DATA SHEET

Application

- ❖ Full synthetic engine oil that offers maximum protection at high temperatures and performance at low temperatures.
- ❖ Specially designed for use in high performance petrol engine applications, but can be used in diesel engines with API CF requirements.
- ❖ Contains superior additive technology to boost performance, with enhanced detergency and stay-in-grade viscometrics.
- ❖ Recommended for all high performance, high revving, turbo charged and supercharged multivalve fuel injected petrol engines found in modern passenger cars and SUVs.

Suitable for use for the following requirements:

- ✓ API SP
- ✓ API CF
- ✓ ACEA A1/B1
- ✓ ILSAC GF-5

Physical Characteristics:

| Properties | | Method | 0W-20 |
|-------------------|--------------------|------------|-------|
| Density @20°C | kg.m ⁻³ | ASTM D4052 | 860 |
| Viscosity @ 40°C | (cSt) | ASTM D445 | 46.3 |
| Viscosity @ 100°C | (cSt) | ASTM D445 | 8.65 |
| Viscosity index | | ASTM D2270 | 167.8 |

Available Product Pack Sizes:

| | Pack Size |
|-----------|-----------|
| OIL-00072 | 4*5L |
| OIL-00073 | 12*1L |
| OIL-00071 | 20L |

Features & benefits

- ❖ Superior sludge and wear protection
- ❖ Advanced detergency and cleaning technology
- ❖ Enhanced viscosity, friction and volatility performance.
- ❖ Low oil consumption
- ❖ Meets the requirements for long-life oils in extended drain applications

Revision 2: July 2023

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD