



TECHNICAL DATA SHEET

PRODUCT

INDY ANTIFREEZE SILICATE FREE Silicate Free Cooling System Protector

DESCRIPTION

INDY Antifreeze Silicate Free is a glycol-based coolant designed to protect automotive engines against corrosion and frost damage. INDY Antifreeze Silicate Free contains corrosion inhibitors suitable for the protection of ferrous and aluminium components in engine cooling systems. INDY Antifreeze Silicate Free is phosphate, nitrate and silicate-free, and is formulated to comply with stringent standards. INDY Antifreeze Silicate Free fulfils requirements as outlined in ASTM D3305 and D4985.

APPLICATION

INDY Antifreeze Silicate Free is suitable for use in a variety of automotive applications. INDY Antifreeze Silicate Free is formulated as a ready to use product, and requires no predilution.

TECHNICAL CHARACTERISTICS

INDY Antifreeze Silicate Free fulfils the following OEM specifications:

Porsche/VW/Audi/Seat/Skoda TL 774D	Mercedes Benz 325.3	Ford ESE M97B48A
Ford WSS M97B44D	Ford ESD M97B49A	Cummins 85T8-2
Cummins 90T8-4	MAN 248 and 324	MAN B&W D36 5600
Wartsilia 32-9011	GM 6277M	GM 1899M
GM QL 130100	Renault 41-01-001	Chrysler MS 9176
Mack 014GS17004	Navistar B-1 Type III	Volvo 260
Leyland LTS AF10	John Deere H24B1 and C1,	Deutz/MWN 0199-2091 2 Auflage CW

Density @ 20°C	kg.m ⁻³	1050	(typical)
Boiling Point @ 760 mmHg	°C	109	
Freezing Point (25% v/v in water)	°C	-12	
Freezing Point (50% v/v in water)	°C	-37	

PACK SIZES

210L, 20L

Revision 2: 27 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.