



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

PRODUCT

INDY LHM FLUID
Central hydraulic system fluid

DESCRIPTION

INDY LHM Fluid is a central hydraulic system fluid designed for hydro pneumatic and self-leveling suspension systems. It is blended from highly refined Group III base oils which have been fortified with selected additives to ensure outstanding performance under the most severe applications. Tests revealed superior hydraulic pump and low temperature performance.

APPLICATION

INDY LHM Fluid is suitable for use in hydraulics systems intended for off-highway applications in agricultural, construction and industrial equipment.

TECHNICAL CHARACTERISTICS

DIN 51524 Part 3

Appearance & Colour		Clear Green	
Density at 20°C	kg.m ⁻³	840	(typical)
Viscosity at 40°C	cSt	18.25	(typical)
Viscosity Index		357	(typical)
Pour Point	°C	< - 50	
Flash Point (PMCC)	°C	195	(min)

PACK SIZES

210 L / 25 L / 20*1L

Revision 2: 16 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD