



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

PRODUCT **INDY ANTIFREEZE & SUMMER COOLANT** Cooling System Protector

DESCRIPTION

INDY Antifreeze and Summer Coolant is a glycol-based coolant designed to protect automotive engines against corrosion and frost damage. INDY Antifreeze and Summer Coolant contains corrosion inhibitors suitable for the protection of ferrous and aluminium components in engine cooling systems, providing extended drain protection of up to 500 000 kms. INDY Antifreeze and Summer Coolant is phosphate, nitrate and silicate-free, and is formulated to comply with stringent international standards.

APPLICATION

INDY Antifreeze and Summer Coolant is suitable for use in both automotive and industrial cooling systems. The required dilution ratio for optimized performance is 1:1 (Indy Antifreeze S/Coolant: water). Indy Antifreeze and Summer Coolant complies with the following regulations and standards:

AS 2108-2004	ASTM D3306	ASTM D4985	SAE J1034
AFNOR NF RS 15-601	ONORM V 5123	CUNA NC 956-16	JIS K 2234:2006
SANS 1251:2005	China GB 29743-2013	BS 6582:2010	

TECHNICAL CHARACTERISTICS

Density @ 20°C	kg.m ⁻³	1110	(typical)
Boiling Point @ 760 mmHg	°C	150	(typical)
Freezing Point (25% v/v in water)	°C	-12	(typical)
Freezing Point (50% v/v in water)	°C	-33	(typical)
Glycol content	%	89	(typical)

Indy Antifreeze and Summer Coolant meets the following OEM requirements:

BMW	BMW GS 94000
Daimler/Mercedes-Benz	MB Approval 325.0
Deutz	DQC CA-14
MAN	MAN 324-NF
MTU	MTL 5048
Opel / General Motors	B 040 0240

Revision 4: 25 February 2019

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

SAAB
VW / Audi / Seat / Skoda
Volvo Truck
MWM
Jenbacher

6901599
TL 774-C
until MY 2005
TR 0199-99-2091-12 DE
TA-Nr. 1000-0201

PACK SIZES

210L, 20L, 20*1L

Revision 4: 25 February 2019

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD