



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

PRODUCT

INDY ANTIFREEZE ANTIBOIL Pre-diluted Antifreeze

DESCRIPTION

INDY Antifreeze Antiboil is a glycol-based coolant designed to protect automotive engines against corrosion and frost damage. INDY Antifreeze Antiboil contains corrosion inhibitors suitable for the protection of ferrous and aluminium components in engine cooling systems, and is pre-diluted as a ready to use formula. INDY Antifreeze Antiboil is suitable for use as a long-life coolant with an extended drain interval of up to 500 000 kms.

APPLICATION

INDY Antifreeze Antiboil is suitable for use in both automotive and industrial cooling systems. No dilution is required before use. INDY Antifreeze Antiboil meets the performance specifications of the following coolant standards:

AS 2108:2004	ASTM D3306	ASTM D4985	SAE J1034
AFNOR NF RS 15-601	ONORM V 5123	CUNA NC 956-16	JIS K 2234:2006
SANS 1251:2005	China GB 29743-2013	BS 6582:2010	

TECHNICAL CHARACTERISTICS

Density @ 20°C	kg.m ⁻³	1110	(typical)
Boiling Point @ 760 mmHg	°C	174	(typical)
Freezing Point (25% v/v in water)	°C	-12	(typical)
Freezing Point (50% v/v in water)	°C	-33	(typical)
Glycol content	%	45	(typical)

INDY Antifreeze Antiboil meets the requirements of the following OEMS:

BMW	BMW GS 94000
Daimler/Mercedes-Benz	MB Approval 325.0
Deutz	DQC CA-14
MAN	MAN 324-NF
MTU	MTL 5048
Opel / General Motors	B 040 0240
SAAB	6901599
VW / Audi / Seat / Skoda	TL 774-C
Volvo Truck	until MY 2005
MWM	TR 0199-99-2091-12 DE
Jenbacher	TA-Nr. 1000-0201

PACK SIZES

210L, 20L, 4*5L, 20*1L

Revision 4:25 February 2019

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.