



TECHNICAL DATA SHEET

PRODUCT

INDY TRAX TO-4 Transmission Oils

DESCRIPTION

INDY Trax TO-4 oils are a range of transmission oils formulated to comply with Caterpillar TO-4 specifications. INDY Trax TO-4 is blended using quality base oils and additive packages to ensure friction control, low gear wear and oxidation stability characteristics required for powershift transmissions.

APPLICATION

INDY Trax TO-4 is suitable for use in heavy duty and off-highway applications requiring Caterpillar and Komatsu specifications. INDY Trax TO-4 is suitable for powershift transmissions, final drive and hydraulic applications.

TECHNICAL CHARACTERISTICS

CAT TO-4 and TO-4M
API MT-1

Allison C4
ZF TE-ML-03C

Komatsu KES 07.868.1 (2002)
ZF TE-ML-07F

SAE Grade		10W	30	40	50	
Density @ 20°C	kg.m ⁻³	880	890	900	900	(typical)
Viscosity @ 40°C	cSt	35	103	150	257	(typical)
Viscosity @ 100°C	cSt	6	10.9	14.8	19.2	(typical)
Viscosity Index		100	95	95	93	

PACK SIZES

210L, 20L

Revision 2: 23 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD