

SUPER TURBO DIESEL

INDY MAX DX VI

Application

SYNTRO

- A fully synthetic automatic transmission fluid comprising advanced additive technology that meets the General Motors' DEXRON-VI specifications.
- Fully back-serviceable, meaning it can be used wherever DEXRON-II and/or DEXRON-III are recommended.
- Principal application is in automatic transmissions of passenger cars, power steering and hydraulic systems.
- Also approved for use in certain transmissions used in commercial road vehicles and off-highway equipment.
- Recommended for use in power steering and hydraulic systems of vehicles and earth moving equipment

Features & benefits

- Enhances the performance of new and older GM transmissions.
- Provides consistent shift performance for the life of the vehicle.
- Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures.
- Provides excellent oxidative stability under severe conditions.
- Reduces sludge and varnish build-up.
- Protects transmission gears and allows them to operate smoothly.
- Maintains lubricity
- Flows well for cold start-up

Revision 01: April 2024

Durban Head Office: + 27 31 910 3111 + 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

TECHNICAL DATA SHEET

Specifications, Approvals & Recommendations:

- Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS)
- ✓ Allison C-3 & C-4
- ✓ American Motors ATF +3 (MS7176-E)
- ✓ Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
- ✓ BMW LT71141 (ZF 5 HP 18FL/19FL/24A)
- ✓ Caterpillar TO-2
- ✓ Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309
- ✓ Daihatsu AMMIX ATF D-II & D-III SP
- ✓ Ford MERCON [®] & FNR5

Physical Characteristics:

Properties		DX VI
Density @20°C	kg.m⁻³	850
Viscosity @40°C	(cSt)	30.24
Viscosity @100°C	(cSt)	6.17
Viscosity Index		158.5

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00678	12*1L

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD