



PRODUCT **INDY AIR**
Air Compressor Oils

DESCRIPTION

INDY Air range is a range of premium oils that are blended from paraffinic base oils and contain a unique blend of ashless additives that incorporate anti-wear, anti-foam and good demulsibility characteristics. The INDY Air range is formulated to provide excellent performance in a wide variety of compressor applications.

APPLICATION

INDY Air range is suitable for use in crankcase and cylinder lubrication of reciprocating air compressors and for rotary vane and screw compressors that require mineral-based lubricants.

TECHNICAL CHARACTERISTICS

DIN 51506 VDL

| | | | | | | |
|--------------------|--------------------|-----|-----|-----|------|-----------|
| ISO Grade | | 32 | 46 | 68 | 100 | |
| Density at 20°C | kg.m ⁻³ | 860 | 870 | 880 | 890 | (typical) |
| Viscosity at 40°C | cSt | 32 | 46 | 68 | 100 | (typical) |
| Viscosity at 100°C | cSt | 5.0 | 7.0 | 8.0 | 11.0 | (typical) |
| Viscosity Index | | 115 | 106 | 103 | 99 | |

PACK SIZES

210L, 25L

Revision 2: 20 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD