

INDY AIR Air Compressor Oils

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name INDY Air

Description The INDY Air range of products are high quality compressor oils,

blended from mineral paraffinic base oils. They contain antiwear, anti-rust, anti- oxidant and anti-foam additives for premium

performance.

Validation Date November 2011

Manufacturer INDY OIL SA (Pty) Ltd

4-6 Platinum Road Montague Gardens

Cape Town South Africa

7435

In Case of Emergency Tel. +27 (21) 552 2330

2. COMPOSITION

INDY Air oils consist of a blend of highly refined mineral base oils and additives. Risk phrases R36 and R38 apply.

3. HAZARDS IDENTIFICATION

Primary hazards and critical effects: No specific hazards under normal conditions of use. Prolonged skin contact may cause dermatitis.

Health risk None known.

Flammability Not classified as a flammable, but will burn.

Reactivity Not applicable.

CAPE TOWN
HEAD OFFICE

HEAD OFFICE JOHANNESBURG DURBAN

Tel: 021 552 2330 Tel: 011 392 3111 Tel: 032 944 1923 Fax: 021 552 2879 Fax: 011 392 3199 Fax: 032 944 4449

MATERIAL SAFETY DATA SHEET - PAGE 2

4. FIRST AID MEASURES

In the event of dizziness or nausea, remove the patient to fresh

air. If symptoms persist, obtain medical attention.

Ingestion Wash out mouth with water and obtain medical attention. Do not

induce vomiting.

Skin Contact May cause irritation with prolonged contact. Remove

contaminated clothing and wash affected skin with soap and water. Obtain medical attention if persistent irritation develops.

Eye Contact Flush eyes with clean water for at least 15 minutes. Get medical

attention if irritation develops.

Advice to Doctor Treat symptomatically. Dermatitis may result from prolonged or

repeated exposure. Aspiration into the lungs may result in

chemical pneumonitis.

5. FIRE -FIGHTING MEASURES

Combustion will form complex mixture of airborne solids and gases including carbon monoxide, oxides and sulphur as well as unidentified inorganic compounds.

Extinguishing media Foam and dry powder. Carbon dioxide, sand or earth may be

used on small fires.

Protective equipment Proper protective equipment, including breathing apparatus

must be worn when approaching a fire in confined space.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid skin and eye contact. Wear protective clothing such as

gloves, rubber boots and safety goggles or face shield.

Environmental precautions Prevent entry into sewers and waterways. Contain

spill by using sand or earth. Inform local authorities if spill cannot

be contained.

Clean-up methods Liquid can be absorbed on inert material. Sweep up and remove

in accordance with local regulations.

7. HANDLING AND STORAGE

Keep container closed. Store in cool, well-ventilated place. Avoid strong oxidising agents.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

Occupational Exposure The control measures appropriate for a particular worksite

depends on how this material is used and the extent of exposure. The best protection is to use the product in well-

ventilated areas.

Personal Protection If engineering controls and work practices are not effective in

controlling this material, then wear suitable personal protection equipment, including safety goggles or face shield, boots, impervious gloves, overalls and breathing apparatus.

CAPE TOWN
HEAD OFFICE

HEAD OFFICE JOHANNESBURG DURBAN

Tel: 021 552 2330 Tel: 011 392 3111 Tel: 032 944 1923 Fax: 021 552 2879 Fax: 011 392 3199 Fax: 032 944 4449

9. PHYSICAL AND CHEMICAL PROPERTIES

Please refer to Product Data Sheet

Physical state Liquid at standard temperature

Appearance Light brown
Density at 20°C ca. 0.88 kg/l
Vapour Pressure < 0.5 Pa at 20°C

Auto-ignition Temperature > 320° Flash Point > 180°C Vapour Density (Air = 1) > 1

Kinematic Viscosity at 40°C Varies between 32 and 100, depending on grade

10. STABILITY AND REACTIVITY

Stability The product is stable
Materials to avoid Strong oxidising agents
Conditions to avoid Extremes of temperatures

11. TOXICOLOGICAL INFORMATION

Toxicological data have not been determined specifically for these oils. The information given is based on knowledge of similar products.

Acute toxicity - Oral LD5

y - Oral LD50 expected to be > 2000 mg/kg - Dermal LD50 expected to be > 2000 mg/kg

Inhalation Not considered a hazard under normal use

Eye Irritation Can be slightly irritating

Skin Irritation Can be slightly irritating upon prolonged exposure.

Respiratory Irritation If mists are inhaled, slight irritation of the respiratory tract may

occur.

Carcinogenicity Not known to be carcinogenic.

Mutagenicity Not considered to be a mutagenetic hazard.

Reproductive toxicity Not considered to be a hazard.

12. ECOLOGICAL INFORMATION

This product is liquid under most environmental conditions. It floats on water and if it enters soil, it will be absorbed to soil particles.

Biodegradability The product is not readily biodegradable.

Bioaccumulation Contains components with the potential to bio accumulate.

Eco toxicity may cause physical fouling of aquatic organisms though product is non-toxic.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with prevailing regulations through a recognised collector or contractor. Do not pollute soil, sewage or waterways with waste product.

14. TRANSPORTATION INFORMATION

INDY Air Oils are not regulated and no special transportation requirements exist.

15. REGULATORY INFORMATION

None of the components are classified in terms of RSA regulation

<u>CAPE TOWN</u>
<u>HEAD OFFICE</u>

<u>JOHANNESBURG</u>

<u>DURBAN</u>

Tel: 021 552 2330 Tel: 011 392 3111 Tel: 032 944 1923 Fax: 021 552 2879 Fax: 011 392 3199 Fax: 032 944 4449

MATERIAL SAFETY DATA SHEET - PAGE 4

16. OTHER INFORMATION

Validated by INDY OIL SA (Pty) Ltd on 7 November 2011 Version 2

This document replaces previous validations.

CAPE TOWN
HEAD OFFICE

Tel: 021 552 2330 Tel: 011 392 3111 Tel: 032 944 1923 Fax: 021 552 2879 Fax: 011 392 3199 Fax: 032 944 4449

JOHANNESBURG

DURBAN