



TECHNICAL DATA SHEET

PRODUCT

INDY SINSA 26
Mould Release Oil

DESCRIPTION

INDY Sinsa 26 is an emulsifiable mould release oil that prevents concrete sticking to moulds or shuttering work. INDY Sinsa 26 produces a smooth finish with no concrete build up on the mould or shutter board, and may be applied by spray, rollers, brush or swabs.

APPLICATION

INDY Sinsa 26 can be used neat or as an emulsion on moulds or shuttering mould from timber, plywood or metal. The recommended dilution (if using as an emulsion) is 3:1 (water: INDY Sinsa 26). The dilution ratio may be increased to 5:1 (water: INDY Sinsa 26) for less critical applications.

Water must always be added to INDY Sinsa 26, and not INYD Sinsa 26 to water. Ensure that the oil is vigorously stirred whilst the water is being slowly added. The liquid should be mixed well until a thin homogenous emulsion is formed.

It is recommended that the emulsion be used on the same day that it was formed, to ensure complete homogeneity during application in the mould.

It is recommended that new moulds be coated with INDY Sinsa 26 with 2 or 3 coatings before use.

INDY SR 101 must be applied as a concentrate to the relevant surface either by brush or spray application.

TECHNICAL CHARACTERISTICS

Density at 20°C	kg.m ⁻³	820	(typical)
Viscosity at 40°C	cSt	23.5	(typical)

PACK SIZES

210L, 20L