



TECHNICAL DATA SHEET

PRODUCT

INDY GUARD 303
De-watering Fluid

DESCRIPTION

INDY Guard 303 is light brown dewatering fluid which on evaporation of the solvent, deposits a thin protective film. INDY Guard 303 has a thin, slightly greasy film characteristic.

APPLICATION

Indy Guard 303 can be used as a mild press lubricant where it gives protection to the work piece without additional treatment. The thin film gives excellent rust protective properties for inter- operational protection. Apply by spray or submersion.

Protection

Indoors - 3 months

Outdoors - 1 month

The period specified for outdoor use assumes primary protection from the elements by tarpaulin or other forms of cover.

A solvent degreasing fluid or suitable alkali cleaner can be used to remove the protective film.

TECHNICAL CHARACTERISTICS

Appearance	Amber fluid
Density at 20°C	0.790 kg/l
Film Thickness (Micrometer)	0.64
Drying Time at 20°C (Minutes)	30
Flash Point (Abel)	40°C

PACK SIZES

210 lt / 25 lt

Revision 2: 20November 2015Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.