



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

PRODUCT

INDY HYDROL RO5 Low Viscosity Hydraulic Fluid

DESCRIPTION

INDY Hydrol RO5 is a low viscosity hydraulic fluid suitable for use in all types of hydraulic pumps, provided there is inadequate viscosity at the bulk operating temperature. INDY Hydrol RO5 has specifically been designed to give good steel-on-steel and steel-on-bronze anti-wear performance. INDY Hydrol RO5 is formulated with ashless antiwear additives, making it suitable for use in pumps containing silver plated bearing and / or valve components

APPLICATION

INDY Hydrol RO5 is suitable for use in forklift trucks operating in cold stores and is also recommended for high speed spindle bearings.

TECHNICAL CHARACTERISTICS

AFNOR NF E 48603
Din 51524 Parts 2 &3
Denison T6C-202
Vickers I-286-S

AFNOR E 48690
Cincinnati P68/69/70
Vickers M-2959-S (35VQ25)

AFNOR E 48691
Denison HF0

ISO Grade		5	
Density @ 20°C	(kg.m ⁻³)	830	(typical)
Viscosity @ 40°C	(cSt)	5.0	(typical)
Viscosity @ 100°C	(cSt)	1.8	(typical)

PACK SIZES

210 L / 20 L

Revision 2: 20 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD