



MATERIAL SAFETY DATA SHEET

INDY HYDROL HV High VI Hydraulic Fluid

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	INDY Hydrol HV
Description	High VI Hydraulic Fluid
Validation Date	November 2015
Manufacturer	GUD Holdings (Pty) Ltd via Indy Oil SA 3 The Avenue East Isipingo KwaZulu-Natal South Africa 4110
Emergency Contact Number	+ 27 31 910 3111 + 27 60 572 8088

2. COMPOSITION

Component	EINECS Number	CAS registry number	% content	Classification
Distillate (Petroleum), Solvent dewaxed, paraffinic	265-157-1	64742-65-0	50 - 95	R36 / R38

DURBAN
HEAD OFFICE

Tel: +27 31 910 3111
Fax: +27 31 902 4889

Pietermaritzburg

Tel: + 27 33 392 9300
Fax: +27 33 390 1844

3. HAZARDS IDENTIFICATION

Human Health Hazards

Causes mild eye cause irritation characterized by a burning sensation. Inhalation of vapour or mist may cause respiratory tract irritation.

The product is harmful if swallowed. Aspiration of the material into the lungs may cause chemical pneumonitis. Ingestion may lead to stomach distress, nausea and vomiting. Repeated contact or exposure to the skin may lead to cracking / drying due to the defatting action of the material. Skin discolouration may occur as a result of prolonged exposure.

Safety Hazards

The product is not classified as flammable, but will burn. Care should be exercised upon storage and handling.

Environmental Hazards

The product may lead to environmental contamination as applicable to those associated with oil spills.

4. FIRST AID MEASURES

General Information

If the product splashes into the eye it may cause irritation and conjunctivitis. Ingestion may lead to irritation of the mouth, throat and digestive tract. Aspiration into the respiratory system may occur directly or following ingestion.

Prolonged exposure to vapour may cause headache, dizziness, nausea and irritation to the eyes, upper respiratory tract, mouth and digestive tract. Obtain medical attention if discomfort continues. Remove affected person from source of contamination.

The following recommendations apply to sources of exposure:

Inhalation

Remove to fresh air, and keep affected person at rest. Obtain medical attention if irritation to respiratory tract is severe and adversely affects breathing.

Ingestion

Rinse out mouth thoroughly. Do not induce vomiting. Obtain medical attention immediately.

Skin Contact

Remove contaminated clothing, and wash skin with soap and water. Clothing must be laundered before reuse. If irritation persists, obtain medical attention.

Eye Contact

Flush eyes with clean water for at least 15 minutes. Do not rub or agitate the affected area.

5. FIRE FIGHTING MEASURES

Hazardous combustion products may include carbon monoxide (CO) and carbon dioxide (CO₂), as well as combustion products of sulphur and nitrogen.

Extinguishing Media:

Foam or dry chemical powder. Carbon dioxide, sand or earth can be used for small fires. Keep containers exposed to the fire

DURBAN
HEAD OFFICE

PIETERMARITZBURG

Tel: +27 31 910 3111
Fax: +27 31 902 4889

Tel: +27 33 392 9300
Fax: +27 33 390 1844

Protective Equipment	cool by spraying with water. The danger zone should be cleared immediately. Proper protective equipment including breathing apparatus must be worn when approaching a fire.
----------------------	--

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid inhalation of vapour and aerosol spray. Avoid contact with eyes, and prolonged skin contact. Ensure adequate ventilation is provided. In the event of a spill, beware of slippery surfaces.
Environmental precautions	Do not allow environmental contamination to occur. Avoid disposal (accidental or incidental) of product into drains, sewers, rivers and other water sources, and onto the ground. Use appropriate spill containment measures to avoid environmental contamination. Inform local authorities if this cannot be prevented. Use sand, earth or other appropriate absorbent material to contain spills. The product should not be dumped, but collected and delivered according to agreement with local authorities.
Spill clean-up / containment	Stop product leak if possible to do so without risk. Extinguish all ignition sources, and ensure adequate ventilation. The product in its liquid form can be contained by creating a barrier using sand, earth or other appropriate containment material. Collect with absorbent, non-combustible material into suitable containers. Do not allow run-off into sewers and drains. Dispose of material according to agreement with local authorities. Inform authorities immediately if the liquid enters surface water sources.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Ensure good personal hygiene when handling product. Wash hands, clothing and other contaminated areas with water and soap before leaving the work site to minimize spread of contamination. Do not eat, drink or smoke when using the product. Avoid forming sprays / aerosol mists. Ensure adequate ventilation is provided when product is being used. Ensure personal protective equipment is used where necessary.

STORAGE CONDITIONS

Store the product in its original container, and ensure that the container is tightly closed and kept upright. Store in a cool, dry, and well-ventilated area. Ensure that the relevant spill containment apparatus is available. Exposure to excessive temperatures should be avoided. Water contamination should be avoided. The product is suitable for short-term storage in mild steel and high density polyethylene (HDPE) containers.

DURBAN
HEAD OFFICE

Tel: +27 31 910 3111
Fax: +27 31 902 4889

PIETERMARITZBURG

Tel: +27 33 392 9300
Fax: +27 33 390 1844

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

The following personal protective equipment is applicable:



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize risk of inhalation of vapour.

RESPIRATORY EQUIPMENT

The use of respiratory equipment under normal operating conditions is not required. Should operating conditions create airborne concentrations that are excessive, the use of an approved respirators such as toxic dust, mist and fume respirators are recommended.

HAND PROTECTION

The use of chemical-resistant, nitrile or butyl rubber gloves is recommended.

EYE PROTECTION

The use of tightly-fitted safety goggles / glasses is recommended when splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

Wash contaminated clothing promptly and before reuse. Wash skin with soap and water upon contamination.

OCCUPATIONAL EXPOSURE

The ACGIH TLV for mineral oil mists is 5 mg.m^{-3} for a time period of 8-hour exposure. A short-term exposure limit of 10 mg.m^{-3} (STEL) is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance	Amber liquid at ambient temperature
Odour	Hydrocarbon
Solubility	Insoluble in water
Vapour density (air = 1)	Heavier than air
Viscosity at 40°C	15 – 100 cSt (dependent on range)
Density at 20°C	850 - 900 kg.m ⁻³ (dependant on range)
Flash Point	> 200°C

10. STABILITY AND REACTIVITY

Stability	The product is stable.
Materials to avoid	Strong oxidising agents, halogens and halogenated compounds
Conditions to avoid	Extremes of temperatures.
Hazardous Decomposition Products	None under normal conditions known

11. TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

The product is not considered hazardous under normal conditions of use. May cause irritation to eyes, and irritation to skin under prolonged exposure or contact.

ROUTES OF ENTRY

Inhalation. Ingestion. Skin or eye contact.

TOXICOLOGICAL DATA

Inhalation	Not considered a hazard under normal use
Eye Irritation	Can be irritating
Skin Irritation	Can be irritating upon prolonged exposure.
Respiratory Irritation	If mists are inhaled, irritation of the respiratory tract may occur.
Carcinogenicity	Not known to be carcinogenic.
Mutagenicity	Not considered to be a mutagenetic hazard.
Reproductive toxicity	Not considered to be a hazard.
Toxicity	Oral, LD50 >5g/kg (rat)

12. ECOLOGICAL INFORMATION

ECOTOXICITY

The product may cause physical fouling of the aquatic environment, and may present risks associated with oil spills.

BIOACCUMULATION

The product has the ability to bioaccumulate. No available data on bioaccumulation.

DEGRADABILITY

No available data on degradability.

DURBAN
HEAD OFFICE

PIETERMARITZBURG

Tel: +27 31 910 3111
Fax: +27 31 902 4889

Tel: +27 33 392 9300
Fax: +27 33 390 1844

13. DISPOSAL CONSIDERATIONS

Waste relating to the product is considered hazardous, and should be disposed off according to regulations as stipulated by local authorities.

14. TRANSPORTATION INFORMATION

The product is not regulated and no special transportation requirements exist.

15. REGULATORY INFORMATION

Risk phrases	R36 / 38
	R10
	R65

16. OTHER INFORMATION

Validated by	: GUD Holdings (Pty) Ltd
Validation date	: November 2015
Revision number	: 03
Revision date	: November 2015

RISK PHRASES IN FULL

R36 / 38 : Irritating to eyes and skin

DURBAN
HEAD OFFICE

Tel: +27 31 910 3111
Fax: +27 31 902 4889

PIETERMARITZBURG

Tel: +27 33 392 9300
Fax: +27 33 390 1844