



PRODUCT

INDY GEAR Extreme Pressure Industrial Gear Oils

DESCRIPTION

Indy Gear oils are a range of industrial gear oils designed for use in industrial gear sets with circulating and splash lubrication. Indy Gear oils are formulated using additives that exhibit good extreme pressure properties and provide wear protection even under shock loading conditions.

APPLICATION

Indy Gear oils are suitable to industrial gear applications requiring the use of extreme pressure lubricants. Indy Gear oils provide good protection to gears and bearings even under shock loads. Indy Gear oils are available in a range of viscosities to suit a wide variety of applications. Indy Gear range fulfils the following performance requirements:

US Steel 224
Agmar 9005-D94
Cincinnati Milacron
Clean Panel Coker
S-200 oxidation tubes

TECHNICAL CHARACTERISTICS

ISO Grade		68	100	150	220	320	460	680	
Density at 20°C	kg.m ⁻³	870	890	880	900	900	900	910	(typical)
Viscosity at 40°C	(cSt)	68	100	150	220	320	460	680	(typical)
Viscosity at 100°C	(cSt)	8.8	11.1	14.4	18.8	24.8	29.6	38	(typical)
Viscosity Index		102	96	95	95	99	92	91	

PACK SIZES

210L, 20L

Revision 3: 19 February 2019

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.