



## TECHNICAL DATA SHEET

### PRODUCT

### INDY LITHIUM COMPLEX GREASE EP2 Lithium Complex Grease

### DESCRIPTION

INDY Lithium Complex Grease EP2 is extremely shear stable and offers a higher than average operating temperature. It is blended from high quality solvent refined oils and incorporates extreme pressure additive as well as corrosion- and oxidation inhibitors.

### APPLICATION

INDY Lithium Complex Grease EP2 has excellent load carrying abilities and resists water action. This grease is designed for a wide variety of service operating conditions to extend service life in heavy duty applications. It is suitable for use in all types of bearings, CV joints, universal joints, gears, cams, lift trucks, plant vehicles and general machinery. INDY Lithium Complex Grease EP2 is especially recommended for anti-friction bearings in heavy duty service and operating conditions where high loads/high speeds are encountered.

### TECHNICAL CHARACTERISTICS

Consistency NLGI	2
Dropping Point °C	250 min
Worked Penetration at 25°C	265 - 295
Water Washout at 38°C	3% max
Recommended operating temperature	-30°C to 160°C

### PACK SIZES

180 kg  
50 kg  
15 kg  
5 kg



Revision 2: 27 November 2015

Durban Head Office: + 27 31 910 3111  
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300  
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD