Flake Roller Grease

DESCRIPTION

Indy Flake Roller grease is made using a blend of high quality petroleum oils and polymers, which produce a tough lubricating film capable of withstanding shock and vibration. This product is designed for heavy-duty service in adverse environments. This blend, together with a shear stable thickening system, provides a uniquely effective seal against loss of grease or contamination from the atmosphere, even where mechanical seals may be damaged. Rust and oxidation inhibiting characteristics are maximized to affords effective rush protection and long life of grease.

APPLICATION

Indy Flake Roller grease is recommended for use in ball and roller bearings, slides, bushings, screws and general lubrication, even where loads may be quite heavy and speeds slow. This grease offers durable resistance to the severe environments of the mining, construction and forest products industries.

Note: This product is not compatible with inorganic base greases. Lubrication intervals should be increased gradually to ensure complete removal of previous lubricants and the establishment of the surface layer of this grease

BENEFITS

- Excellent adhesive and cohesive characteristics.
- Highly resistant to mechanical shearing.
- Compounded to give optimum protection and long life to seals, as well as forming a protective barrier in damaged seals.

TECHNICAL CHARACTERISTICS

Consistency NLGI

2

Colour (Visual)

Black/Gray Grease

Viscosity @ 40°C

860

Thickener Type

Lithium

Worked Penetration, mm/10

265 - 295

PACK SIZES

15 kg

Revision 2: 13 February 2018

Durban Head Office: + 27 31 910 3111

+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

+27 33 390 184

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.