



TECHNICAL DATA SHEET

PRODUCT **OPEN GEAR & WIRE ROPE LUBRICANT**
Solvent Based Open Gear & Wire Rope Lubricant

DESCRIPTION

INDY Open Gear & Wire Rope Lubricant is a viscous, black, solvent based open gear and wire rope lubricant with excellent adhesive properties to resist fling-off. It functions under heavy duty and shock load conditions, providing a durable lubricating film. The product also provides good water resistance and rust protection.

APPLICATION

INDY Open Gear & Wire Rope Lubricant can be used for the lubrication of large gears of ball mills, rill mills, etc. Open gears, wire ropes, chains and splines as well as railroad traction motor gears requiring an adhesive product.

TECHNICAL CHARACTERISTICS

Operating Temperature	(°C)	95 (max)
Worked Penetration at 25°C	mm	345 - 370
Colour	visual	Black
Viscosity @ 100°C	cSt	260 (after solvent evaporates)

PACK SIZES

15 kg

Revision 2: 13 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD