



WORLD CLASS LUBRICANTS

TECHNICAL DATA SHEET

PRODUCT

INDY COPPER GREASE
Copper-filled Grease

DESCRIPTION

INDY Copper Grease is a NLGI 2 consistency non-melt anti-seize grease with a Bentonite thickener. It ensures an outstanding anti-seize and sealing grease for general maintenance and installation procedures used in industrial, mining and marine applications. The product contains anti-rust, anti-oxidant and extreme pressure additives.

APPLICATION

INDY Copper Grease is designed as an anti-seize compound for use in all types of high pressure joints. When used on threads it does not alter torque requirements. It also helps to prevent fretting corrosion on shafts and bearings.

TECHNICAL CHARACTERISTICS

NLGI	2
Appearance	Bronze
Worked Penetration at 25°C	310-340
Dropping Point	None
Viscosity of Base Oil at 40°C	130 cSt
Solid Lubricants	Copper, Zinc, Molybdenum Disulphide and Graphite

PACK SIZES

5 kg

Revision 2: November 2018 Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD