

**PRODUCT** 

# INDY CUT Neat extreme pressure cutting oils

## **DESCRIPTION**

INDY Cut (F1, F3 and F6) range is a range of concentrated metalworking fluids formulated from mineral oils and containing extreme pressure additives. INDY Cut is recommended for use as a neat oil for the machining of both ferrous and non-ferrous metals.

# **APPLICATION**

INDY Cut range is suitable for the machining of ferrous and non-ferrous metals in applications requiring a light to medium viscosity fluid.

## **TECHNICAL CHARACTERISTICS**

Product		F1	F3	F6	
Appearance		Dark Brown	Dark Brown	Dark Brown	
Density at 20°C	kg.m <sup>-3</sup>	870	880	890	(typical)
Viscosity at 40ºC	cSt	22	33	60	(typical)
Pour Point	ºC	-7	-12	-14	
Flash Point	∘C	202	196	162	

#### **PACK SIZES**

210L, 20L

Revision 2: 27November 2015

Durban Head Office: + 27 31 910 3111

+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300 +27 33 390 1844

+27 33 390 184

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.