



PRODUCT

INDY ALLCUT UV BLE Multipurpose Universal Oil

DESCRIPTION

INDY Allcut UV is a multipurpose lubricant blended from paraffinic base oils designed for use in metal cutting and machine tool lubrication. INDY Allcut UV is formulated with a blend of additives to exhibit excellent extreme pressure characteristics and low foaming tendencies.

APPLICATION

INDY Allcut UV is suitable for use in machining where automatic single and multi-spindle types are applicable. INDY Allcut UV may be used as a hydraulic fluid in these types of machines, and is suitable for machining both ferrous and non-ferrous metal types.

Refer to the table below for metal compatibilities:

	Cast Iron	Low Carbon Steel	High Carbon Steel	Alloy Steel	Stainless Steel	Copper Alloys	Aluminium
Drilling	v	O	Ø	Ø	Ø	v	O
Milling	v	O	Ø	Ø	Ø	v	O
Tapping	v	O	Ø	Ø	Ø	v	O
Turning	v	O	Ø	Ø	Ø	v	O

v = SUITABLE

O = MAY BE SUITABLE

Ø = NOT SUITABLE

TECHNICAL CHARACTERISTICS

Appearance		Amber liquid	
Density at 20°C	kg.m ⁻³	860	(typical)
Viscosity at 40°C	cSt	22.0	(typical)

PACK SIZES

1000L, 210L, 20L

Revision 2: 26 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD