



TECHNICAL DATA SHEET

PRODUCT

INDY TOOLUBE Pneumatic Machinery Lubricants

DESCRIPTION

INDY Toolube is a range of premium quality pneumatic machinery lubricants that are blended from highly refined paraffinic base oils and incorporate special additives to enhance its properties. The oils provide excellent lubrication and anti-wear performance as well as high levels of corrosion protection. Its low pour point ensure that tools remain free from oil deposits in areas cooled by rapid air expansion.

APPLICATION

INDY Toolube can be used in air driven rock drills and other pneumatic machinery. They are specifically designed to have good demulsifying characteristics so that adequate lubrication is still provided even in the presence of wet air.

TECHNICAL CHARACTERISTICS

ISO Grade		150	220	
Density at 20°C	kg.m ⁻³	900	900	(typical)
Viscosity at 40°C	cSt	150	220	(typical)
Viscosity at 100°C	cSt	14.90	20	(typical)
Viscosity Index		99	105	
Pour Point	°C	-9	-6	
Flash Point	°C	248	280	

PACK SIZES

210 L / 20 L

Revision 2: 27 November 2015

Durban Head Office: + 27 31 910 3111
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.

INFORMATION SUPPLIED BY GUD HOLDINGS (Pty) LTD