


# DYNATORQ 15W-40 CK-4/SN

## Product description

Indy Dynatorq 15W-40 CK-4/SN is formulated with advanced additive technology and premium base stock as an ultra-high-performance heavy-duty diesel engine oil that meet the latest API CK-4 standards.

## Applications

- Indy Dynatorq 15W-40 CK-4/SN is backward compatible meaning that it can be safely used in older engines that previously required CJ-4, CI-4, or CH-4 lubricants.

- Indy Dynatorq 15W-40 CK-4/SN can be used in mobile and stationary equipment. It is ideal for mixed fleet engines, construction, mining, agricultural and industrial equipment, providing excellent wear protection and oil consumption control.

## Features & benefits

**Thermal stability**

- Indy Dynatorq 15W-40 CK-4/SN is formulated to handle higher operating temperatures, extreme pressures, and the demands of advanced emission control systems such as Diesel Particulate Filters (DPFs), Exhaust Gas Recirculation (EGR), and Selective Catalytic Reduction (SCR),

**Refined Engine Cleanliness**

- Elevated levels of additives like calcium, zinc, boron, and phosphorus offer improved wear and corrosion control therefore extending engine life and protects critical components.

**Advanced Engine Protection**

- Indy Dynatorq 15W-40 CK-4/SN is designed with low-ash technology to provide a heavy-duty lubricant that delivers exceptional performance with increased oxidative stability, resistance to aeration, shear stability and an improvement in fuel economy.

**Emission control systems compatibility**

- Indy Dynatorq 15W-40 CK-4/SN is able to maintain efficiency in engines with emission control technologies, reducing soot and ash buildup in DPFs.

## Dynatorq 15W-40 CK-4/SN is approved for the following specifications:

- ✓ ACEA E11-22 (2022)
- ✓ API CK-4
- ✓ API SN
- ✓ DTFR 15C100
- ✓ ACEA E11-24 (2024)
- ✓ ACEA E9-16 (2016)
- ✓ ACEA E7-16 (2016
- ✓ API FA-4
- ✓ API CK-4/SN
- ✓ API CJ-4
- ✓ API CI-4 PLUS
- ✓ Cummins CES 20086
- ✓ Cummins CES 20087
- ✓ Detroit Diesel DDC 93K223
- ✓ Detroit Diesel DDC 93K222
- ✓ Renault Truck RLD-3
- ✓ Mack EO-S-4.5
- ✓ Volvo VDS-4.5
- ✓ CAT ECF-3
- ✓ FORD WSS-M2C171-F1
- ✓ MTU Type 2.1
- ✓ Deutz DQC III-10 LA
- ✓ DEUTZ DQC III-18 LA

**G.U.D. Holdings Durban**
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

**G.U.D. Holdings Pietermaritzburg**
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.




- ✓ ALLISON TES-439 (M)
- ✓ JASO DH-2
- ✓ MAN M 3775

## Physical Characteristics:

| Properties | | 15W-40 CK-4 |
|---|---|---|
| Density @20°C | $kg.m^{-3}$ | 863 |
| Viscosity @40°C | (cSt) | 109.41 |
| Viscosity @100°C | (cSt) | 15.09 |
| Viscosity Index | | 144.06 |
| Total Base Number | mg·KOH/g | 10.4 |

## Available Product Pack Sizes:

| Part No. | Pack Size |
|---|---|
| OIL-00198 | 1000L |
| OIL-00201 | 210L |
| OIL-00200 | 20L |
| OIL-00200AM | 20L |
| OIL-00199 | 4*5L |
| OIL-00202 | 12*1L |
| OIL-00203 | 20*500 mL |

**G.U.D. Holdings Durban**
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

**G.U.D. Holdings Pietermaritzburg**
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.