

GREASE EP2

Product description

Indy Grease EP 2 is manufactured using highly refined mineral base oils which are carefully selected and then fortified with synthetic polymers, using a lithium Calcium thickener to produce a highly shear stable foundation for the grease. It is manufactured to a NLGI 2 grade resulting in a grease of medium to soft consistency.

Application

- Recommended for the lubrication of heavily loaded plain and rolling-element bearings, pins, bushes, pivots and other machinery components operating under high loads, shock loading and vibration.
- Suitable for mining, quarrying, construction, cement, steel, agricultural and general heavy-duty industrial equipment, including crushers, conveyors, mills and other slow- to moderate-speed machinery.
- Optimal operating conditions for this grease in terms of temperature, is from -30 to 1300 degrees celcuis, however short periods of elevated temperatures can be tolerated without severe damage to the product.

Features & benefits

- Contains a blend of synthetic tackifiers, increasing its ability to resist water and adherence with all surfaces.
- Formulation includes a full treat of extreme pressure (EP) and corrosion preventative additives enabling the grease to meet or exceed internationally recognized performance standards.
- Very good thermal stability allowing the grease to perform for short periods of time under extreme temperatures, regaining its original texture after cooling to ambient temperature.
- Allows for long periods of storage or non-use in the application without and mechanical breakdown of the grease thickener (e.g. oil separation).

Specifications:

- ✓ ASTM D-5864/CEC L-33-T-82
- ✓ KPHCON-40 (DIN 51825)
- ✓ ISO-L-X-DDIBO (ISO 6743-9)

Typical Characteristics:

DESCRIPTION	METHOD	UNITS	RESULT
NLGI Grade	ASTM D 217		2
Thickener Type			Li-Ca
Colour	Visual		Tan
Appearance	Visual		Buttery, Tacky
Penetration	ASTM D 217	0.1mm	280
Dropping point	ASTM D 2265	°C	190
Viscosity of Oil @ 40°C	ASTM D 2983	cSt	460
4-Ball Wear Test Scar	ASTM D 2266	mm	0.45
4-Ball Weld Load	ASTM D 2596	kg	315
Timken OK Load	ASTM D 2509	lb	45
Corrosion Prevention	ASTM D 1743		Pass
Copper Strip Corrosion	ASTM D 4048		1B

Available Product Pack Sizes:

Part No.	Pack Size
OIL-01374	12*500 G
OIL-01373	4.5 KG
OIL-01372	15 KG
OIL-01371	50 KG
OIL-01370	180 KG

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111
03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.