

GREASE LX3

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier and uses of the substance or mixture

Product Name	Indy Grease LX3
Description	Lithium Calcium Grease EP2 (460cSt)
Relevant uses	Mining, quarrying, construction, cement, steel, paper, agricultural, transport and general industrial equipment

1.2 Details of the supplier of the safety data sheet

Manufacturer	Tribolube Lubricants (PTY) Ltd, 8 Stockville Road, Mahogany Ridge, Durban, South Africa

1.3 Emergency telephone number

Emergency Contact Number(s)	+ 27 31 910 3111 + 27 60 572 8088

2. COMPOSITION

Component	EINECS Number	CAS registry number	% content	Classification
Distillate (Petroleum), Solvent dewaxed, paraffinic	265-169-7	64742-65-0	70 - 95	R36 / R38
Mineral oil and additives	232-455-8	8042-47-5	0.5-30	R36/R38
Stearate	231-536-5	1592-23-0	5-25	R36/R38

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

3. HAZARDS INDENTIFICATION

Emergency Overview

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation

Physical State: Grease

Odor: Petroleum Odor.

Potential Health Effects:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.
Skin Contact:	Lubricating oils are generally considered no more than minimally irritating to the skin.
Eye Contact:	Lubricating oils are generally considered no more than minimally irritating to the eyes. May cause slight irritation of the eyes.
Ingestion Irritation:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Ingestion Toxicity:	Lubricating oils are generally no more than slightly toxic if swallowed.

Long-Term (Chronic)

Reproductive:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Skin Contact:	Prolonged and repeated contact may result in defatting and drying of the skin that may cause various skin disorders such as dermatitis, folliculitis, or oil

HMIS Ratings:

Health: 1

Flammability: 1

Reactivity: 0

PPE: B

0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

4. FIRST AID MEASURES

General Information

If the product splashes into the eye it may cause irritation and conjunctivitis. Ingestion may lead to irritation of the mouth, throat and digestive tract. Aspiration into the respiratory system may occur directly or following ingestion. The product has the potential to be fatal if large amounts are swallowed.
Prolonged exposure to vapour may cause headache, dizziness, nausea and irritation to the eyes, upper respiratory tract, mouth and digestive tract. Obtain medical attention if discomfort continues. Remove affected person from source of contamination.

The following recommendations apply to sources of exposure:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained

individual administer oxygen. Get medical attention immediately.

Eyes: Flush with water. If irritation occurs, get medical attention. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling occur, transport to

nearest medical facility for additional treatment.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irriation occurs, get

medical attention. Do not reuse clothing until cleaned. If redness, swelling, pain, and/or blisters occur, transport to the nearest medical facility for

additional treatment.

Ingestion: Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS.

Notes to Doctor: Aspiration during swallowing or vomiting may severely damage the lungs.

5. FIRE FIGHTING MEASURES

Flammability Summary: Combustible at elevated temperatures

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid.

Fire and/or Explosion

Hazards: Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire. Material may be ignited

only if preheated to temperatures above the high flash point, for example in a fire.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Hazardous Combustion: Carbon dioxide, Carbon monoxide, Products.

Flash point: 220 °C

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling: Mildly irritating material. Avoid unnecessary exposure.

Storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Do not expose to extreme temperatures or flames.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

The following personal protective equipment is applicable:



Engineering measures:	No special requirements.
Respiratory protection:	No special requirements.
Eye protection:	Wear safety glasses when handling this product.
Skin protection:	Gloves should be worn.
Exposure limits:	N/A

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance	Brown paste, grease	
Odour	Petroleum	
pH	ND	
Viscosity	460	cSt @40 °C
Solubility	Insoluble in water	
Specific gravity	0.86-0.90	
Flash point	220	°C
Color	Tan	

10. STABILITY AND REACTIVITY

No hazardous decomposition of products if stored and handled as prescribed.

Stability	Stable
Conditions to avoid	High Temperatures
Incompatibity	Store away from oxidizing agents

11. TOXICOLOGICAL INFORMATION

Oral:	RATS Almost non-toxic (LD50 > 2000mg/kg)
Inhalation:	None
Eyes:	None
Skin:	None

12. ECOLOGICAL INFORMATION

Degradation potential	No experimental data on the final product. Does contain mineral or sythentic oil which is degradeable Degradation potential over time.
Further Information	This product is considered as dangerous to ground flora.

13. DISPOSAL CONSIDERATIONS

Disposal of Packaging:	Recycle containers whenever possible.

Disposal Methods:	Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

14. TRANSPORTATION INFORMATION

Special Information:	DOT & IMDG: NOT RESTRICTED

15. REGULATORY INFORMATION

Labelling:	The product is classified as non-hazardous
Water hazard class	N.E.

16. OTHER INFORMATION

Validated by	: Tribolube Lubricants (PTY) Ltd
Validation date	: September 2026
Revision number	: 01
Revision date	: September 2026

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation