



TECHNICAL DATA SHEET



INDY GREASE MS2

Application

- ❖ Designed for use in highly loaded plain and roller bearings as well as for shock loading conditions. It is suitable for use in the full range of bearing speeds encountered in electric motors, machine and woodworking tools, production equipment, textile and paper-making industry, generators and all types of vehicles.
- ❖ Recommended for all normal applications at ambient temperatures and where conditions are more severe with higher temperatures.

Features & benefits

❖ Refined Engine Cleanliness

Resistant to water and high-temperature steam and suitable for operating temperatures between -30°C and 130°C

❖ Advanced Engine Protection

High quality, multipurpose lithium-based grease made from solvent refined mineral oils and incorporating a multifunctional extreme pressure additive as well as corrosion and oxidation inhibitors.

Physical Characteristics:

Properties		
Soap type	-	Li
Viscosity @40 C	cSt	200
Timken oil load	kg	27
Appearance	Visual	Brown
Dropping point	°C	230 min
Worked penetration @25 C	mm	220-250
Wear washout @38 C	%	3 max
Recommended operating temperature	°C	-30-160

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00736	180KG
OIL-00737	50KG
OIL-00738	15KG
OIL-00739	4.5KG
OIL-00740	500G*20