



TECHNICAL DATA SHEET



INDY MAX CVT FLUID

Application

- ❖ Formulated to provide superior metal to metal friction performance and extended anti-shudder durability.
- ❖ Designed for use on continuously variable transmissions, covering a wide range of transmission configurations.
- ❖ Designed for use as a multi-vehicle fluid suitable for use across a broad range of chain and belt CVTs.

Features & benefits

❖ Refined Engine Cleanliness

Formulated with premium synthetic base stock and special long-life friction modifiers, anti-wear agents and viscosity modifiers to ensure smoother consistent all-weather step-less shifting, as well as increased protection of all transmission components.

Product has excellent low temperature performance characteristics, as well as improved oxidation and thermal stability for a long-life, durable fluid over a wide range of operating conditions.

Product has improved anti-shudder durability, with excellent wet clutch performance with reduced noise, vibration and hardness.

Suitable for use for the following specifications:

- ✓ OEM
- ✓ TL 52180, 52516
- ✓ EZL 799A
- ✓ Ammix CVTF-DC, DFE
- ✓ CVTF+4
- ✓ WSS-M2C933-A
- ✓ Ford MERCON C, M2C928-A
- ✓ DEX-CVT, GM CVT
- ✓ Honda CVT Fluid / Multi Matic Fluid (HMMF), HCF-2
- ✓ SP CVT-1
- ✓ CVTF 3320
- ✓ MB-Approval 236.20
- ✓ Mitsubishi Dia Queen CVTF J1, J4, Diamond ATF SP III
- ✓ Nissan NS-1, NS-2, NS-3
- ✓ Subaru e-CVT, Lineartronic CV-30, CVTF-II, High torque CVTF & i-CVT F
- ✓ Suzuki CVT Fluid Green1, Green2 & CVTF 3320
- ✓ Toyota TC, FE, WS

Physical Characteristics:

Properties		
Density @20°C	kg.m ⁻³	840
Viscosity @40°C	(cSt)	35.1
Viscosity @100°C	(cSt)	7.10
Viscosity Index		160

Available Product Pack Sizes:

Part No.	Pack Size
OIL-01900	12*1L