



## TECHNICAL DATA SHEET



### INDY PROTORQ 5W30 SN/CF

#### Application

- ❖ Specially formulated, high SAPs motor oil, recommended for use in modern petrol and diesel engines.
- ❖ Formulated with uniquely blended additives and synthetic base material to provide exceptional performance in terms of wear protection and prevents deposits and sludge build-up for longer engine life.
- ❖ Recommended for use in a wide range of modern vehicles (petrol and diesel engines), with or without turbo-charging where a 5W30 oil is required, and in passenger cars and delivery vans with extended oil drain intervals.

#### Suitable for use for the following specifications:

- ✓ API SN/CF
- ✓ ACEA C3
- ✓ Land Rover STJLR.03.5003
- ✓ Ford WSS M2C 913-C
- ✓ Ford WSS M2C 913-B
- ✓ MB 229.51
- ✓ VW 504 00 / 507 00
- ✓ BMW LL-04

#### Physical Characteristics:

Properties	SAE 5W30
Density @20°C	kg.m <sup>-3</sup>
Viscosity @40°C	(cSt)
Viscosity @100°C	(cSt)
Viscosity Index	

#### Features & benefits

- ❖ A lower fuel consumption
- ❖ A fast-cold start
- ❖ A safe lubrication film at high temperatures
- ❖ Extended oil drain intervals
- ❖ Excellent detergency and dispersion
- ❖ Enhanced protection against wear, corrosion and foaming.

#### Available Product Pack Sizes:

Part No.	Pack Size
OIL-00136	210L
OIL-00137	20L
OIL-00138	4*5L
OIL-00139	20*500ML