

INDY

TECHNICAL DATA SHEET



INDY PROTORQ 5W30 SN/CF

Application

- ❖ Specially formulated, mid SAPs motor oil recommended for use in modern petrol and diesel engines, and suitable for vehicles that are fitted with after treatment devices (DPFs)
- ❖ Formulated with uniquely blended additives and synthetic base material to provide exceptional performance in terms of wear protection and prevents deposits and sludge build-up for longer engine life.
- ❖ Recommended for use in a wide range of modern vehicles (petrol and diesel engines), with or without turbo-charging where a 5W30 oil is required, and in passenger cars and delivery vans with extended oil drain intervals.

Features & benefits

- ❖ A lower fuel consumption
- ❖ Suitable for vehicles fitted with DPFs
- ❖ A fast-cold start
- ❖ A safe lubrication film at high temperatures
- ❖ Excellent detergency and dispersion
- ❖ Enhanced protection against wear, corrosion and foaming.

Suitable for use for the following specifications:

- ✓ API SN/CF
- ✓ ACEA C3
- ✓ Land Rover STJLR.03.5003
- ✓ Ford WSS M2C 913-C
- ✓ Ford WSS M2C 913-B
- ✓ MB 229.51
- ✓ VW 504 00 / 507 00
- ✓ BMW LL-04

Physical Characteristics:

Properties		SAE 5W30
Density @20°C	kg.m ⁻³	850
Viscosity @40°C	(cSt)	69.2
Viscosity @100°C	(cSt)	12.0
Viscosity Index		171
HTHS		3.3

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00136	210L
OIL-00137	20L
OIL-00138	4*5L
OIL-00139	20*500ML