



TECHNICAL DATA SHEET

SUPER TURBO DIESEL 15W40 CI-4/SL

Application

- ❖ High performance engine oil specially formulated with advanced additive technology.
- ❖ Suitable for modern diesel and petrol engines, buses, trucks and industrial equipment.
- ❖ Suitable for use in long-service conditions in both turbocharged and normally aspirated heavy-duty engines.
- ❖ Service intervals range up to 15 000 km or 300 hours for normal duty diesel engines*.

* depends on application type, operating conditions, and manufacturer recommendations

Features & benefits

❖ Refined Engine Cleanliness

Formulated with advanced additives incorporating anti-wear, detergency and corrosion inhibition functionalities to ensure that maximum protection against sludging and provide excellent engine cleanliness.

❖ Advanced Engine Protection

Formulated to provide excellent stay-in-grade viscometrics even when operating under severe conditions provides excellent corrosion protection even with high sulphur levels, has a high level of wear protection and resistance to bore polishing.

Suitable for use in the following applications:

- ✓ DIESEL – API CI-4, CH-4, CG-4
- ✓ PETROL – API SL, SJ, SH
- ✓ ACEA A3/B4
- ✓ MAN M3275-1
- ✓ MB 228.3/229.1
- ✓ VOLVO VDS 3
- ✓ CAT ECF-1-A/ECF-2
- ✓ MTU DDC TYPE 2
- ✓ MACK EO-N, EO-M PLUS
- ✓ GLOBAL DHD-1
- ✓ RENAULT RLD/RLD-2
- ✓ DEUTZ DQC III
- ✓ ALLISON C4
- ✓ DETROIT DDC 93K 215
- ✓ CUMMINS CES 2007/6/7/8
- ✓ JASO DH-1

Physical Characteristics:

Properties	15W40 CI-4
Density @ 20°C	kg.m-3
Viscosity @ 40°C	(cSt)
Viscosity @ 100°C	(cSt)
Viscosity Index	
Pour point	°C
Flash point	°C
Total Base Number	mg KOH/g

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00156	1000L
OIL-00157	210L
OIL-00158	20L
OIL-00159	4*5L
OIL-00160	12*1L
OIL-03366	20*500ML