

LHM FLUID

Product description

Indy LHM Fluid is a central hydraulic system fluid designed for hydro pneumatic and self-leveling suspension systems. It is blended from highly refined Group III base oils which have been fortified with selected additives to ensure outstanding performance under the most severe applications. Tests revealed superior hydraulic pump and low temperature performance.

Application

- Formulated for hydraulic braking, power steering, suspension and levelling systems that require an LHM-type fluid.
- Suitable for use in hydraulics systems intended for off-highway applications in agricultural, construction and industrial equipment.

Features & benefits:

- **Advanced Protection**
  Blended from highly refined synthetic base oils which have been fortified with selected additives to ensure outstanding performance under the most severe applications.
- **Optimized Thermal Stability**
  Field tests revealed superior hydraulic pump and low temperature performance.

Physical Characteristics:

Properties		
Appearance	Liquid	Clear green
Density @20°C	$kg.m^{-3}$	840
Viscosity @40 °C	(cSt)	22.3
Viscosity @100 °C	(cSt)	5.95
Viscosity index		270
Pour point	°C	-58
Flash point	°C	195 min

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00826	20*1L

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.