

MAX CVT FLUID

Product description

Indy Max CVT Fluid is specially formulated to provide superior metal to metal friction performance and extended anti-shudder durability.

Application

- Designed for use on continuously variable transmissions, covering a wide range of transmission configurations.

- Designed for use as a multi-vehicle fluid suitable for use across a broad range of chain and belt CVTs.

Features & benefits

- **Refined Engine Cleanliness**
  Formulated with premium synthetic base stock and special long-life friction modifiers, anti-wear agents and viscosity modifiers to ensure smoother consistent all-weather step-less shifting, as well as increased protection of all transmission components.

  Product has excellent low temperature performance characteristics, as well as improved oxidation and thermal stability for a long-life, durable fluid over a wide range of operating conditions.

  Product has improved anti-shudder durability, with excellent wet clutch performance with reduced noise, vibration and hardness.

Physical Characteristics:

Properties		
Density @20°C	$kg.m^{-3}$	840
Viscosity @40°C	(cSt)	35.1
Viscosity @100°C	(cSt)	7.10
Viscosity Index		160

Available Product Pack Sizes:

Part No.	Pack Size
OIL-01900	12*1L

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.