

MAX DX III H

Product description

Indy Max DX III H is a full synthetic automatic transmission fluid, designed for use in transmissions, power steering and hydraulic systems where a DX-III fluid is specified. Indy Max DX III H is formulated to provide excellent performance and a long service life.

Application

- Recommended for older systems that call for Dexron II or earlier Dexron III fluids.
- Used in passenger cars, light trucks, and heavy-duty highway vehicles requiring GM Dexron III or Ford Mercon standards.
- Acts as a high-performance fluid for automotive and commercial power steering pumps.
- Utilized in select manual transmission units where manufacturers specify a light ATF.

Features & benefits

- Formulated with an additive technology incorporating excellent frictional properties and film strength in high temperature applications.
- Provides good protection against power steering pump wear.

Suitable for use for the following specifications:

- ✓ Allison C4
- ✓ Ford Mercon
- ✓ GM Dexron III
- ✓ Caterpillar TO-2
- ✓ M2C 138 CJ/ 166 H

Physical Characteristics:

Properties		
Density @20°C	$kg.m^{-3}$	840
Viscosity @40°C	(cSt)	31.7
Viscosity @100°C	(cSt)	7.0
Viscosity Index		194

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00665	210L
OIL-00666	20L
OIL-00666AM	20L
OIL-00667	20*500mL

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.