

MONOGRADE SAE 30 & 40

Product description

Monograde SAE 30 and 40 are mineral-based single-grade engine oils formulated to provide reliable lubrication and protection for petrol engines operating under a range of service conditions. Monograde SAE 30 and 40 viscosity grades provide effective lubrication and oil-film strength at operating temperatures.

Application

- Suitable for older petrol engines, stationary engines, generators, agricultural equipment, industrial engines and other applications where a monograde SAE 30 or SAE 40 API SG engine oil is specified by the equipment manufacturer.

Features & benefits

- **Advanced Additive Package**
  Formulated from base oils that have been fortified with the latest additive technology. These additives incorporate anti-wear, anti-oxidant and corrosion inhibition functionalities.

Suitable for use for the following specifications:

- ✓ API SG/CF

Physical Characteristics:

Properties		SAE Grade 30	SAE Grade 40
Density @20°C	$kg.m^{-3}$	880	890
Viscosity @40°C	(cSt)	100	143
Viscosity @100°C	(cSt)	11.4	14.2
Viscosity Index		95	95

Available Product Pack Sizes:

Part No. 30	Part No. 40	Pack Size
OIL-00088	OIL-00097	210L
-	OIL-00098	20L (BUCKET)
-	OIL-00098AM	20L
OIL-00089	OIL-00095	20L (CAN)
-	OIL-00099	4*5L
-	OIL-00099-IR	4*5L
-	OIL-00100	12*1L
-	OIL-00101	20*500ML
	OIL-00101-IR	20*500ML

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.