



INDY

SAFETY DATA SHEET

INDY MONOGRADE SAE 40

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	INDY Monograde SAE 40
Description	Monograde Premium Motor Oil
Validation Date	June 2024
Manufacturer	GUD Holdings (Pty) Ltd via Indy Oil SA 3 The Avenue East Isipingo KwaZulu-Natal South Africa 4110
Emergency Contact Number	+ 27 31 910 3111 + 27 60 572 8088

2. HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Not classified.

2.2 Label elements

Signal Word	No Signal word
Hazard statements	H318 Causes serious eye damage

SAFETY DATA SHEET – PAGE 2

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement

P102 Keep out of reach of children.

Prevention

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response

P302 + P352 If on skin: Wash with plenty of water.

P310 Immediately call a doctor

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

Storage

Not applicable.

Disposal

P501 Dispose of contents / container in accordance with local / regional / national / international regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS:

Component	EINECS Number	CAS registry number	% content	Classification
Distillate (Petroleum), Solvent dewaxed, paraffinic	265-157-1	64742-54-7	60 - 80	H319 / H318
Sulfur-phosphorous- dioctyl alkyl zinc salt	-	26566-95-0	≥10 - <20	H411, H318, H315
2-ethylpentyl 3-(3,5-di- tert-butyl-4- hydroxyphenyl) propanoate	-	68783-96-0	≥1.0 - <5.0	H413

Methyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	228-985-4	6386-38-5	<0.5	H411
1-[N,N-bis-(2-ethyl-hexyl)aminomethyl] tolutriazole	-	-	<0.01	H315, H317, H411

4. FIRST AID MEASURES

General Information

If the product splashes into the eye it may cause irritation and conjunctivitis. Ingestion may lead to irritation of the mouth, throat and digestive tract. Aspiration into the respiratory system may occur directly or following ingestion.

Prolonged exposure to vapour may cause headache, dizziness, nausea and irritation to the eyes, upper respiratory tract, mouth and digestive tract. Obtain medical attention if discomfort continues. Remove affected person from source of contamination.

The following recommendations apply to sources of exposure:

Inhalation

Remove to fresh air, and keep affected person at rest. Obtain medical attention if irritation to respiratory tract is severe and adversely affects breathing.

Ingestion

Rinse out mouth thoroughly. Do not induce vomiting. Obtain medical attention immediately.

Skin Contact

Remove contaminated clothing, and wash skin with soap and water. Clothing must be laundered before reuse. If irritation persists, obtain medical attention.

Eye Contact

Flush eyes with clean water for at least 15 minutes. Do not rub or agitate the affected area.

5. FIRE FIGHTING MEASURES

Hazardous combustion products may include carbon monoxide (CO) and carbon dioxide (CO₂), as well as combustion products of sulphur and nitrogen.

Extinguishing Media:	Foam or dry chemical powder. Carbon dioxide, sand or earth can be used for small fires. Keep containers exposed to the fire cool by spraying with water. The danger zone should be cleared immediately.
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Protective Equipment	Proper protective equipment including breathing apparatus must be worn when approaching a fire.
----------------------	-------------------------------------------------------------------------------------------------

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid inhalation of vapour and aerosol spray. Avoid contact with eyes, and prolonged skin contact. Ensure adequate ventilation is provided. In the event of a spill, beware of slippery surfaces.
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Environmental precautions	Do not allow environmental contamination to occur. Avoid disposal (accidental or incidental) of product into drains, sewers, rivers and other water sources, and onto the ground. Use appropriate spill containment measures to avoid environmental contamination. Inform local authorities if this cannot be prevented. Use sand, earth or other appropriate absorbent material to contain spills. The product should not be dumped, but collected and delivered according to agreement with local authorities.
---------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Spill clean-up / containment

Stop product leak if possible to do so without risk. Extinguish all ignition sources, and ensure adequate ventilation. The product in its liquid form can be contained by creating a barrier using sand, earth or other appropriate containment material. Collect with absorbent, non-combustible material into suitable containers. Do not allow run-off into sewers and drains. Dispose of material according to agreement with local authorities. Inform authorities immediately if the liquid enters surface water sources.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Ensure good personal hygiene when handling product. Wash hands, clothing and other contaminated areas with water and soap before leaving the work site to minimize spread of contamination. Do not eat, drink or smoke when using the product. Avoid forming sprays / aerosol mists. Ensure adequate ventilation is provided when product is being used. Ensure personal protective equipment is used where necessary.

STORAGE CONDITIONS

Store the product in its original container, and ensure that the container is tightly closed and kept upright. Store in a cool, dry, and well-ventilated area. Ensure that the relevant spill containment apparatus is available. Exposure to excessive temperatures should be avoided. Water contamination should be avoided. The product is suitable for short-term storage in mild steel and high-density polyethylene (HDPE) containers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

The following personal protective equipment is applicable:



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize risk of inhalation of vapour.

RESPIRATORY EQUIPMENT

The use of respiratory equipment under normal operating conditions is not required. Should operating conditions create airborne concentrations that are excessive, the use of an approved respirators such as toxic dust, mist and fume respirators are recommended

HAND PROTECTION

The use of chemical-resistant, nitrile or butyl rubber gloves is recommended.

EYE PROTECTION

The use of tightly-fitted safety goggles / glasses is recommended when splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

Wash contaminated clothing promptly and before reuse. Wash skin with soap and water upon contamination.

OCCUPATIONAL EXPOSURE

The ACGIH TLV for mineral oil mists is 5 mg.m⁻³ for a time period of 8-hour exposure. A short-term exposure limit of 10 mg.m⁻³ (STEL) is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical appearance

Colour

Odour

Solubility

Liquid at ambient temperature

Amber

Hydrocarbon

Insoluble in water

Vapour density (air = 1)	Heavier than air
Viscosity at 40°C (kinematic)	132 cSt (typical)
Viscosity at 100°C (kinematic)	14.75 cSt (typical)
Density at 20°C	890 kg.m ⁻³ (typical)
Flash Point	>240 °C

10. STABILITY AND REACTIVITY

Chemical stability	Stable.
Reactivity	Not reactive.
Materials to avoid	Strong oxidising agents.
Conditions to avoid	Extremes of temperatures.
Hazardous Decomposition Products	None under normal conditions known.

11. TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

The product is not considered hazardous under normal conditions of use. May cause irritation to eyes, and irritation to skin under prolonged exposure or contact.

ROUTES OF ENTRY

Inhalation. Ingestion. Skin or eye contact.

TOXICOLOGICAL DATA

Inhalation	Not considered a hazard under normal use.
Eye Irritation	Can be slightly irritating.
Skin Irritation	Can be slightly irritating upon prolonged exposure.
Respiratory Irritation	If mists are inhaled, slight irritation of the respiratory tract may occur.
Carcinogenicity	Not known to be carcinogenic.
Mutagenicity	Not considered to be a mutagenetic hazard.
Reproductive toxicity	Not considered to be a hazard.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

The product may cause physical fouling of the aquatic environment, and may present risks associated with oil spills.

BIOACCUMULATION

The product has the ability to bioaccumulate. No available data on bioaccumulation.

DEGRADABILITY

No available data on degradability.

13. DISPOSAL CONSIDERATIONS

Waste relating to the product is considered hazardous, and should be disposed of according to regulations as stipulated by local authorities.

14. TRANSPORTATION INFORMATION

The product is not regulated and no special transportation requirements exist.

15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

European Union – European Inventory of Existing Commercial Chemical Substances (EINECS) (English).

Chemical Safety Assessment

No data available.

16. OTHER INFORMATION

Full text of H-Phrases

H319	Causes serious eye irritation.
H318	Risk of serious damage to eyes.
H315	Causes skin irritation.

SAFETY DATA SHEET – PAGE 9

H317	May cause an allergic skin reaction.
H411	Hazardous to the aquatic environment, long-term hazard
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Abbreviations that may have been used in this document

GHS	Global Harmonised System
-----	--------------------------

Further information

Validated by	: GUD Holdings (Pty) Ltd
Validation date	: June 2024
Revision number	: 02
Revision date	: June 2024

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.