

QUANTEC PLUS 10W-40 SN

Product description

Indy Quantec Plus 10W-40 SN is a high-performance semi-synthetic multi-grade engine oil formulated to provide reliable protection and performance in both petrol and diesel engines. Indy Quantec Plus 10W-40 SN provides good low-temperature fluidity for reliable cold starting while maintaining a strong lubricating film at elevated operating temperatures.

Application

- Suitable for passenger cars, light commercial vehicles, trucks, buses and other petrol and diesel engines requiring API SN and/or CI-4 performance, including naturally aspirated and turbocharged engines where specified by the manufacturer.
- Suitable for use in petrol and diesel engines fitted to light delivery vehicles.

Features & benefits

- **Advanced Additive Package**
  Offers enhanced lubrication and engine protection by incorporating an additive blend that employs anti-wear, corrosion inhibition, anti-foam and detergency functionalities.

  Lower in viscosity than conventional passenger car engine oils and flows easier through the engine under cold starting conditions, ensuring better protection and improved fuel efficiency in comparison to conventional 20W-50 and 15W-40 engine oils

- **Advanced engine protection**
  Contains unique anti-wear additives that protect the engine consistently and is specifically formulated to provide a thick cushion of lubrication to protect hard working engines.

  Contains unique anti-oxidation additives that optimize protection by extending the life of the oil, and combats excessive engine and bearing wear.

  Provides excellent detergency to ensure cleanliness of components, high performance and long service life.

Suitable for use for the following specifications:

- ✓ API: SN/CI-4
- ✓ ACEA A3/B3/B4/E7
- ✓ MB 229.1
- ✓ VW 501.01, 502.00, 505.00; Mack EO-M Premium Plus
- ✓ Cummins CES 20078
- ✓ Global DHD-1
- ✓ ACEA E3-96 (issue 3)
- ✓ ACEA ES-99
- ✓ DB 228.3
- ✓ Navistar

Physical Characteristics:

Properties		10W-40 SN
Density @20°C	$kg.m^{-3}$	860
Viscosity @40°C	(cSt)	89.9
Viscosity @100°C	(cSt)	14.3
Viscosity Index		165

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00028	1000L
OIL-00029	210L
OIL-00030	20L
OIL-00030AM	20L
OIL-00031	4*5L
OIL-00031-IR	4*5L
OIL-00032	12*1L
OIL-00033	20*500ML

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.