

SUPER TURBO DIESEL 15W-40 CI-4/SL

Product description

Indy Super Turbo Diesel 15W-40 CI-4/SL is a heavy-duty mineral-based multi-grade engine oil formulated to provide reliable lubrication and protection for diesel engines operating under demanding conditions. Its viscosity grade provides good cold-start performance together with a robust lubricating film at elevated operating temperatures.

Application

- High-performance heavy-duty diesel engine oil specially formulated with advanced additive technology.
- Suitable for modern diesel and petrol engines, buses, trucks and industrial equipment.
- Suitable for use in long-service conditions in both turbo-charged and normally aspirated heavy-duty engines.
- Service intervals range up to 15 000 km or 300 hours for normal duty diesel engines*.

**dependent on application type, operating conditions, and manufacturer recommendations

Features & benefits

- **Refined Engine Cleanliness**

Formulated with advanced additives incorporating anti-wear, detergency and corrosion inhibition functionalities to ensure that maximum protection against sludging and provide excellent engine cleanliness.

- **Advanced Engine Protection**

Formulated to provide excellent stay-in-grade viscometrics even when operating under severe conditions provides excellent corrosion protection even with high sulphur levels, has a high level of wear protection and resistance to bore polishing.

Suitable for use in the following applications:

- ✓ API CI-4/SL
- ✓ ACEA A3/B3
- ✓ MAN M3275
- ✓ MB 228.3/229.1
- ✓ Volvo VDS 3
- ✓ CAT ECF-1-a/ECF-2
- ✓ MTU Type 2
- ✓ Mack EO-N, EO, M PLUS
- ✓ Global DHD 1
- ✓ Renault VI RLD-2
- ✓ DEUTZ DQC111-10
- ✓ ALLISON C4 LEVEL
- ✓ Detroit DDC 93K 215
- ✓ JASO DH-0

Physical Characteristics:

Properties		15W-40 CI-4
Density @20°C	kg.m-3	880
Viscosity @40°C	(cSt)	112
Viscosity @100°C	(cSt)	15.5
Viscosity Index		135
Pour point	°C	-35
Flash point	°C	221
Total Base Number	mg KOH/g	10.7

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00156	1000L
OIL-00157	210L
OIL-00158	20L
OIL-00158AM	20L
OIL-00159	4*5L
OIL-00159-IR	4*5L
OIL-00160	12*1L
OIL-03366	20*500 mL
OIL-03366-IR	20*500 mL

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.