

SUPER TWO STROKE OIL

Product description

Indy Super Two-Stroke Engine Oil is a high-quality lubricant blended from paraffinic mineral oils and a specially formulated additive combination to provide high levels of detergency and deposit control, as well as exhibiting excellent lubricity and dispersancy characteristics. Indy Super Two-Stroke Engine Oil is designed for use in high-performance two-stroke engines.

Application

- Suitable for 2-stroke motorcycles, scooters, generators, chainsaws, brush cutters and other small engines where an API TC performance level is specified.
- Suitable for use in both oil injection auto lubricant systems and premix applications.

Features & benefits

- **Advanced Additive Technology**
  Reduced deposits due to low ash detergent dispersant additives. Controls ash and carbon deposits while maintaining combustion efficiency and protection against power loss even under severe conditions. The carrier oil / additive combination ensures a stable fuel/oil mix for long periods of time.
- **Gear Wear Protection**
  Excellent lubricity characteristics of the low ash additive system and superior anti wear additives protect and prevent wear under high speed conditions.
- **System longevity**
  Indy Super Two-Stroke Engine Oil prevents fouling and prolongs the life of the spark plug. The carrier oil / additive combination ensures a stable fuel/oil mix for long periods of time.

Suitable for use for the following specifications:

- ✓ API TC
- ✓ JASO MA (T903:2006)
- ✓ JASO MA2

Physical Characteristics:

Properties		SAE 40
Density @20°C	$kg.m^{-3}$	870
Viscosity @40°C	(cSt)	103
Viscosity @100°C	(cSt)	14.3
Viscosity Index		165
Sulphated ash	%	0.85
Evaporative loss	%	15
Phosphorus content	%	0.09
Dynamic Friction Characteristic Index		1.90
Static Friction Characteristic Index		1.90
Foam Tendency (Sequence I/II/III)		10/40/8
Foam Stability (Sequence I/II/III)		0/0/0

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00339	210L
OIL-00340	20L
OIL-00340AM	20L
OIL-00342	12*1L
OIL-00341	4*5L
OIL-00347	20*500 mL
OIL-00346	20*200 mL

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111
03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa
G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844
info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.