

ULTRATEC 5W-40 SN/CF

Product description

Indy Ultratec 5W-40 is a Synthetic based engine oil specially designed for use in both high-performance petrol and diesel engines.

Application

- Recommended for all high revving, turbo charged and supercharged multivalve fuel injected petrol and diesel engines found in modern passenger cars and SUVs.

Features & benefits

- **Refined Engine Cleanliness**

  Formulated with superior additive technology which boosts performance, provides enhanced detergency and stay-in-grade viscometrics.

  Offers the following benefits:
  - A lower fuel consumption
  - A fast cold start
  - A safe lubrication film at high temperatures
  - Extended oil drain intervals

- **Advanced Engine Protection**
  - Excellent detergency and dispersion
  - Enhanced protection against wear, corrosion and foaming

Suitable for use for the following specifications:

- ✓ API SN/CF
- ✓ ACEA A3 /B3
- ✓ Ford WSS M2C 913B
- ✓ MB 229.52
- ✓ VW 502 00 / 505 00
- ✓ BMW LL-01
- ✓ GM LL-B-025
- ✓ RN 710 / 700

Physical Characteristics:

Properties		5W-40
Density @20°C	$kg.m^{-3}$	860
Viscosity @40°C	(cSt)	86
Viscosity @100°C	(cSt)	16
Viscosity Index		154

Available Product Pack Sizes:

Part No.	Pack Size
OIL-00020	1000L
OIL-00021	210L
OIL-00022	20L
OIL-00022AM	20L
OIL-00023	4*5L
OIL-00023-IR	4*5L
OIL-00024	12*1L
OIL-00025	20*500ML

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.