

ULTRATEC 5W-40

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier and uses of the substance or mixture

Product Name	Indy Ultratec 5W-40
Description	Multigrade Petrol Engine Oil
Relevant uses	High-performance petrol and diesel engines

1.2 Details of the supplier of the safety data sheet

Manufacturer	GUD Holdings (Pty) Ltd via Indy Oil SA 3 The Avenue East Isipingo KwaZulu-Natal South Africa 4110

1.3 Emergency telephone number

Emergency Contact Number(s)	+ 27 31 910 3111 + 27 60 572 8088

2. HAZARDS INDENTIFICATION

2.1 Classification of substance or mixture

Product definition Mixture.

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Aquatic Chronic 2, H411

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.

See Section 11 for more detailed information on health effects and symptoms.

See Section 12 for environmental precautions.

See Section 16 for the full text of the H statements declared above**.**

2.2 Label elements

Hazard pictograms



Signal Word None.

Hazard statements

Causes skin irritation.

Causes serious eye damage.

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

Wear protective gloves.

Wear eye or face protection.

Avoid release to the environment.

Response

Collect spillage.

IF IN EYES: Contact with eyes can cause serious damage, including blindness. Symptoms may include pain, tearing, reddening, swelling and impaired vision. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF ON SKIN: repeated with skin may cause irritation. Symptoms may include pain, itching, discolouration and swelling. Wash with plenty of soap and water.

Storage Store in a well-ventilated place.

Disposal Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

Elements Contains calcium sulphonate. May produce an allergic reaction.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB

---

3. COMPOSITION/INFORMATION ON INGREDIENTS:

Component	EINECS Number	CAS registry number	% content	Classification
Distillate (Petroleum), Solvent dewaxed, paraffinic	265-157-1	64742-54-7	60 - 80	H319 / H318
Zinc alkyl dithiophosphate	-	26566-95-0	10-20	H315-H412/413
Long Chained Calcium Sulphonate	-	68783-96-0	20-30	H317-H413

---

4. FIRST AID MEASURES

General Information

If the product splashes into the eye it may cause irritation and conjunctivitis. Ingestion may lead to irritation of the mouth, throat and digestive tract. Aspiration into the respiratory system may occur directly or following ingestion.

Prolonged exposure to vapour may cause headache, dizziness, nausea and irritation to the eyes, upper respiratory tract, mouth and digestive tract. Obtain medical attention if discomfort continues. Remove affected person from source of contamination.

The following recommendations apply to sources of exposure:

Inhalation	Remove to fresh air, and keep affected person at rest. Obtain medical attention if irritation to respiratory tract is severe and adversely affects breathing.
Ingestion	Rinse out mouth thoroughly. Do not induce vomiting. Obtain medical attention immediately.
Skin Contact	Remove contaminated clothing, and wash skin with soap and water. Clothing must be laundered before reuse. If irritation persists, obtain medical attention.
Eye Contact	Flush eyes with clean water for at least 15 minutes. Do not rub or agitate the affected area.

5. FIRE FIGHTING MEASURES

Hazardous combustion products may include carbon monoxide (CO) and carbon dioxide (CO_2), as well as combustion products of sulphur and nitrogen.

Extinguishing Media:	Foam or dry chemical powder. Carbon dioxide, sand or earth can be used for small fires. Keep containers exposed to the fire cool by spraying with water. The danger zone should be cleared immediately.
Protective Equipment	Proper protective equipment including breathing apparatus must be worn when approaching a fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid inhalation of vapour and aerosol spray. Avoid contact with eyes, and prolonged skin contact. Ensure adequate ventilation is provided. In the event of a spill, beware of slippery surfaces.
Environmental precautions	Do not allow environmental contamination to occur. Avoid disposal (accidental or incidental) of product into drains, sewers, rivers and other water sources, and onto the ground. Use appropriate spill containment measures to avoid environmental

	contamination. Inform local authorities if this cannot be prevented. Use sand, earth or other appropriate absorbent material to contain spills. The product should not be dumped, but collected and delivered according to agreement with local authorities.
Spill clean-up / containment	Stop product leak if possible to do so without risk. Extinguish all ignition sources, and ensure adequate ventilation. The product in its liquid form can be contained by creating a barrier using sand, earth or other appropriate containment material. Collect with absorbent, non-combustible material into suitable containers. Do not allow run-off into sewers and drains. Dispose of material according to agreement with local authorities. Inform authorities immediately if the liquid enters surface water sources.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Ensure good personal hygiene when handling product. Wash hands, clothing and other contaminated areas with water and soap before leaving the work site to minimize spread of contamination. Do not eat, drink or smoke when using the product. Avoid forming sprays / aerosol mists. Ensure adequate ventilation is provided when product is being used. Ensure personal protective equipment is used where necessary.

STORAGE CONDITIONS

Store the product in its original container, and ensure that the container is tightly closed and kept upright. Store in a cool, dry, and well-ventilated area. Ensure that the relevant spill containment apparatus is available. Exposure to excessive temperatures should be avoided. Water contamination should be avoided. The product is suitable for short-term storage in mild steel and high-density polyethylene (HDPE) containers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

The following personal protective equipment is applicable:



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize risk of inhalation of vapour.

RESPIRATORY EQUIPMENT

The use of respiratory equipment under normal operating conditions is not required. Should operating conditions create airborne concentrations that are excessive, the use of an approved respirators such as toxic dust, mist and fume respirators are recommended

HAND PROTECTION

The use of chemical-resistant, nitrile or butyl rubber gloves is recommended.

EYE PROTECTION

The use of tightly-fitted safety goggles / glasses is recommended when splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

Wash contaminated clothing promptly and before reuse. Wash skin with soap and water upon contamination.

OCCUPATIONAL EXPOSURE

The ACGIH TLV for mineral oil mists is 5 $mg.m^{-3}$ for a time period of 8-hour exposure. A short-term exposure limit of 10 $mg.m^{-3}$ (STEL) is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical appearance	Liquid at ambient temperature
Colour	Amber
Odour	Hydrocarbon
Solubility	Insoluble in water
Vapour density (air = 1)	Heavier than air

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.

Viscosity at 40ºC (kinematic)	94 cSt	(typical)
Viscosity at 100ºC (kinematic)	15.5 cSt	(typical)
Density at 20ºC	870 $kg.m^{-3}$	(typical)
Flash Point	>220 °C	

10. STABILITY AND REACTIVITY

Chemical stability	Stable.
Reactivity	Not reactive
Materials to avoid	Strong oxidising agents
Conditions to avoid	Extremes of temperatures.
Hazardous Decomposition Products	None under normal conditions known

11. TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

The product is not considered hazardous under normal conditions of use. May cause irritation to eyes, and irritation to skin under prolonged exposure or contact.

ROUTES OF ENTRY

Inhalation. Ingestion. Skin or eye contact.

TOXICOLOGICAL DATA

Inhalation	Not considered a hazard under normal use
Eye Irritation	Can be slightly irritating
Skin Irritation	Can be slightly irritating upon prolonged exposure.
Respiratory Irritation	If mists are inhaled, slight irritation of the respiratory tract may occur.
Carcinogenicity	Not known to be carcinogenic.
Mutagenicity	Not considered to be a mutagenetic hazard.
Reproductive toxicity	Not considered to be a hazard.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

The product may cause physical fouling of the aquatic environment, and may present risks associated with oil spills.

BIOACCUMULATION

The product has the ability to bioaccumulate. No available data on bioaccumulation.

DEGRADABILITY

No available data on degradability.

13. DISPOSAL CONSIDERATIONS

Waste relating to the product is considered hazardous, and should be disposed off according to regulations as stipulated by local authorities.

14. TRANSPORTATION INFORMATION

The product is not regulated and no special transportation requirements exist.

15. REGULATORY INFORMATION

Hazard phrases	H319/318/315/317/412/413
Safety phrases	P101, P102

16. OTHER INFORMATION

Full text of H-Phrases

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Risk of serious damage to eyes.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of P-Phrases

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of the reach of children.

Further information

Validated by	: GUD Holdings (Pty) Ltd
Validation date	: August 2026
Revision number	: 02
Revision date	: August 2026

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za