

VORTEX 0W-20 SP/CF

Product description

Indy Vortex 0W-20 is a full synthetic engine oil that offers maximum protection at high temperatures and performance at low temperatures. It is specially designed for use in high performance petrol engine applications, but can be used in diesel engines with API CF requirements.

Application

- Contains superior additive technology to boost performance, with enhanced detergency and stay-in-grade viscometrics.
- Recommended for all high performance, high revving, turbo charged and supercharged multivalve fuel injected petrol engines found in modern passenger cars and SUVs.

Features & benefits

- Superior sludge and wear protection
- Advanced detergency and cleaning technology
- Enhanced viscosity, friction and volatility performance.
- Low oil consumption
- Meets the requirements for long-life oils in extended drain applications

Suitable for use for the following requirements:

- ✓ API SP/CF
- ✓ ILSAC GF-5 / GF-6A
- ✓ GM dexos 1™: 2015 (gen 2)
- ✓ Chrysler MS6395
- ✓ Ford WSS-M2C947-B1 / WSS-M2C962-A

Physical Characteristics:

Properties		Method	0W-20
Density @20°C	$kg.m^{-3}$	ASTM D4052	860
Viscosity @ 40°C	(cSt)	ASTM D445	46.3
Viscosity @ 100°C	(cSt)	ASTM D445	8.65
Viscosity index		ASTM D2270	167.8

Available Product Pack Sizes:

	Pack Size
OIL-00071	20L
OIL-00072	4*5L
OIL-00073	12*1L

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.